

## Tristar KA-5215 Calefactor eléctrico (Mica)

Marca : Tristar

Código del producto: KA-5215

Nombre del producto : KA-5215 Calefactor eléctrico (Mica)

- Termostato ajustable y potencia máxima de 1500 W
- 3 ajustes diferentes
- Utiliza calentamiento micatérmico
- Su uso es seguro gracias a la protección contra sobrecalentamiento y al interruptor de seguridad antivuelco

Tristar KA-5215 Calefactor eléctrico (mica), 3 ajustes, Termostato ajustable

Tristar KA-5215 Calefactor eléctrico (Mica). Adecuado para: Interior, Opciones de colocación: Piso, Color del producto: Negro. Potencia de calentamiento: 1500 W, Potencia de calentamiento (min): 500 W.

Voltaje de entrada AC: 220 - 240 V, Frecuencia de entrada AC: 50 Hz, Tipo de enchufe: Tipo J. Ancho: 705 mm, Profundidad: 155 mm, Altura: 655 mm



| Características                            |           | Desempeño                       |             |
|--|-----------|---------------------------------|-------------|
| Número de niveles de potencia              | 3         | Potencia de calentamiento *     | 1500 W      |
| Interruptor de encendido/apagado integrado | ✓         | Potencia de calentamiento (min) | 500 W       |
| Interruptores de Seguridad                 | ✓         | Ajustes de termostato *         | ✓           |
| Protección contra sobrecalentamiento       | ✓         | Control de energía              |             |
| Protección anti-tilt                       | ✓         | Voltaje de entrada AC           | 220 - 240 V |
| Diseño                                     |           | Frecuencia de entrada AC        | 50 Hz       |
| Adecuado para *                            | Interior  | Tipo de enchufe                 | Tipo J      |
| Opciones de colocación *                   | Piso      | Peso y dimensiones              |             |
| Color del producto *                       | Negro     | Ancho                           | 705 mm      |
| Luz de indicación                          | ✓         | Profundidad                     | 155 mm      |
| Tipo de control                            | Giratorio | Altura                          | 655 mm      |
| Rueda de reenvío                           | ✓         | Contenido del embalaje          |             |
|  |           | Manual de usuario               | ✓           |



8713016088116

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 08-APR-2024. Prints or copies of Information are only valid on the printed Publication date