



EM 30 2 G A L

EASY



Modular gas hob

- Stainless steel
- Enamelled grid
- Auto-ignition
- Auto-lock safety device
- Metal looking frontal knobs
- 2 cooking zones:
- 1 fast burner (3 kW)
- 1 auxiliary burner (1 kW)
- Gas typology: LPG (butane/propane), natural

FRAME
Stainless Steel

EXTERNAL DIMENSIONS

510 mm 300 mm



EM 30 2 P - T

EASY



Modular electric hob

- Stainless steel
- Timer (60 min.)
- Metal looking frontal knobs
- 2 cooking zones:
- 1 electric plate 180 mm Ø (1.5 kW)
- 1 electric plate 145 mm Ø (1.5 kW)
- Max. nominal power: 3000 W
- Gas typology: LPG (butane/propane), natural
- Optional: junction kit

FRAME
Stainless Steel

EXTERNAL DIMENSIONS

510 mm 300 mm



EM 30 2 P

EASY

Modular electric hob

- Stainless steel
- Metal looking frontal knobs
- 2 cooking zones:
- 1 electric plate 180 mm Ø (1.5 kW)
- 1 electric plate 145 mm Ø (1.5 kW)
- Max. nominal power: 3000 W
- Gas typology: LPG (butane/propane), natural
- Optional: junction kit

FRAME
Stainless Steel

EXTERNAL DIMENSIONS

510 mm 300 mm



MODEL	IRF 9480 TFT	IT 6450 IK-B	IT 6350 IK-B	IRC 9430 KS	IR 9400 HS
FEATURES					
Type	Induction	Induction	Induction	Induction	Induction
Touch Control	7" Touch screen color	IK-B Touch Control	iK-B Touch Control	Slider	•
Space Induction	SPACE	-	-	-	-
Frame	Bevelled glass	Slim metal frame	Slim metal frame	Bevelled	Bevelled
Cooking time programmer	•	•	•	•	•
Synchro function	-	•	-	•	-
Power Plus function	•	•	•	•	•
Power function	•	•	•	•	•
Stop&Go function	•	•	•	•	-
Pan optimization system	•	•	•	•	•
Power management function	•	•	•	-	•
Mute Function	•	•	•	-	-
Pan detector	•	•	•	•	•
Low-temp function	-	-	-	•	•
COOKING DIRECT FUNCTIONS					
iQuickBoiling	•	•	•	•	-
Simmering	•	-	-	-	-
Melting	•	-	-	-	-
Keep Warm	•	•	•	-	-
SAFETY SYSTEMS					
Residual heat indicator	•	•	•	•	•
Safety blocking	•	•	•	•	•
Automatic safety disconnection	•	•	•	•	•
COOKING ZONES					
Front left	Ø 280 2.300-3.700 W	Ø 145 1.400-1.800 W	Ø 145 1.400-1.800 W	Ø 280 2300-3700 W	Ø 210 2.300-3.200 W
Front middle	Ø 145 1.400-1.800 W	-	Ø 190/300 2.500-3.700 W	Ø 145 1400-1800 W	Ø 145 1400-1800 W
Front right	Flex 270 x 180 mm. 1.850-2.500 W	Ø 180 1.850 W-2.500 W	-	Ø 180 1800-2500 W	Ø 180 1850-2500 W
Rear left	-	Ø 210 2.300-3.200 W	Ø 210 2.300-3.200 W	-	-
Rear middle	-	-	-	Ø 180 1800-2500 W	Ø 180 1850-2500 W
Rear right	Flex 270 x 180 mm. 1.850-2.500 W	Ø 180 1.850-2.500 W	-	-	-
HOB PERFORMANCE (ACCORDING TO EU 66/2014 REGULATION)					
Ø19/30 cm ECElectric cooking-Induction, Wh/Kg	-	-	172	-	-
Ø28 cm ECElectric cooking-Induction, Wh/Kg	172	-	-	172	-
Ø18/28 cm ECElectric cooking-Induction, Wh/Kg	-	-	-	-	-
Ø26 cm ECElectric cooking-Induction, Wh/Kg	-	-	-	-	-
Ø21 cm ECElectric cooking-Induction, Wh/Kg	-	178	178	-	178
Ø18 cm ECElectric cooking-Induction, Wh/Kg	-	189	-	189	189
Ø14,5 cm ECElectric cooking-Induction, Wh/Kg	202	202	202	202	202
27 x 18 cm ECElectric cooking-Induction, Wh/Kg	Area Flex=194,3 Individual= 188,5	-	-	-	-
23,5 x 19 cm ECElectric cooking-Induction, Wh/Kg	-	-	-	-	-
Ø12/19 cm ECElectric cooking-Radiant heater, Wh/Kg	-	-	-	-	-
Energy consumption for the whole hob, Wh/Kg	189	190	184	188	190
EXTERNAL DIMENSIONS					
Width, mm	900	605	605	950	900
Depth, mm	510	515	515	520	400
BUILT-IN DIMENSIONS					
Width, mm	860	560	560	930	860
Depth, mm	490	490	490	500	380
ELECTRICAL FEATURES					
Voltage, V	230	230	230	230	230
Frequency, HZ	50/60	50/60	50/60	50/60	50/60
Maximum connection rating, W	7.400	7.400	7.400	7.400	7.400
Cable connection length, cm	110	110	110	150	110

MODEL	IR 9330 HS	IR 9530	IB 9530	IRF 9430	IR 8430
FEATURES					
Type	Induction	Induction	Induction	Induction	Induction
Touch Control	Slider	Slider	Slider	Slider	Slider
Space Induction	-	-	-	SPACE	-
Frame	Bevelled	Bevelled	Bevelled	Bevelled	Bevelled
Cooking time programmer	*	*	*	*	*
Synchro function	-	*	*	-	*
Power Plus function	*	*	*	*	*
Power function	*	*	*	*	*
Stop&Go function	*	*	*	*	*
Pan optimization system	*	*	*	*	*
Power management function	-	-	-	-	-
Mute Function	-	-	-	-	-
Pan detector	*	*	*	*	*
Low-temp function	*	*	*	*	*
ICOOKING DIRECT FUNCTIONS					
iQuickBoiling	*	*	*	*	*
Simmering	-	-	-	-	-
Melting	-	-	-	-	-
Keep Warm	-	*	*	-	*
SAFETY SYSTEMS					
Residual heat indicator	*	*	*	*	*
Safety blocking	*	*	*	*	*
Automatic safety disconnection	*	*	*	*	*
COOKING ZONES					
Front left	Ø 180/280 2500-3700 W	Ø 145 1400-1800 W	Ø 145 1400-1800 W	Ø 280 2300-3700 W	Ø 280 2.300- 3.700 W
Front middle	Ø 145 1400-1800 W	Ø 190/300 2500 / 3700 W	Ø 190/300 2500 / 3700 W	Ø 145 1400-1800 W	Ø 145 1400-1800 W
Front right	Ø 210 2.300-3.200 W	Ø 180 1800-2500 W	Ø 180 1800-2500 W	Flex 270 x 180 mm. 1.850-2.500 W	Ø 180 1850-2500 W
Rear left	-	Ø 210 2.300-3.200 W	Ø 210 2.300-3.200 W	-	-
Rear middle	-	-	-	-	-
Rear right	-	Ø 180 1800-2500 W	Ø 180 1800-2500 W	Flex 270 x 180 mm. 1.850-2.500 W	Ø 180 1850-2500 W
HOB PERFORMANCE (ACCORDING TO EU 66/2014 REGULATION)					
ø19/30 cm ECElectric cooking-Induction, Wh/Kg	-	172	172	-	-
ø28 cm ECElectric cooking-Induction, Wh/Kg	-	-	-	172	172
ø18/28 cm ECElectric cooking-Induction, Wh/Kg	172	-	-	-	-
ø26 cm ECElectric cooking-Induction, Wh/Kg	-	-	-	-	-
ø21 cm ECElectric cooking-Induction, Wh/Kg	178	178	178	-	-
ø18 cm ECElectric cooking-Induction, Wh/Kg	-	184	184	-	189
ø14,5 cm ECElectric cooking-Induction, Wh/Kg	202	202	202	202	202
27 x 18 cm ECElectric cooking-Induction, Wh/Kg	-	-	-	Area Flex=194,3 Individual= 188,5	-
23,5 x 19 cm ECElectric cooking-Induction, Wh/Kg	-	-	-	-	-
ø12/19 cm ECElectric cooking-Radiant heater, Wh/Kg	-	-	-	-	-
Energy consumption for the whole hob, Wh/Kg	184	184	184	189	188
EXTERNAL DIMENSIONS					
Width, mm	900	900	900	900	800
Depth, mm	400	510	510	510	510
BUILT-IN DIMENSIONS					
Width, mm	860	830	830	830	750
Depth, mm	380	490	490	490	490
ELECTRICAL FEATURES					
Voltage, V	230	230	230	230	230
Frequency, HZ	50/60	50/60	50/60	50/60	50/60
Maximum connection rating, W	7.400	11.000	11.000	7.400	7.400
Cable connection length, cm	110	110	110	110	110

MODEL	IR 8400	IR 8300 HS	IR 721	IR 720	IZF 6424
FEATURES					
Type	Induction	Induction	Induction	Induction + High light	Induction
Touch Control	Slider	*	*	*	Multislider PRO
Space Induction	-	-	-	-	SPACE
Frame	Bevelled	Bevelled	Bevelled	Bevelled	Frontal Bevelled
Cooking time programmer	*	*	*	*	*
Synchro function	-	-	-	-	-
Power Plus function	*	*	-	-	-
Power function	*	*	*	*	*
Stop&Go function	-	-	-	-	*
Pan optimization system	*	*	*	-	*
Power management function	-	*	-	-	*
Mute Function	-	*	-	-	*
Pan detector	*	*	*	*	*
Low-temp function	*	*	-	-	-
ICOOKING DIRECT FUNCTIONS					
iQuickBoiling	-	-	-	-	-
Simmering	-	-	-	-	*
Melting	-	-	-	-	*
Keep Warm	-	*	-	-	*
SAFETY SYSTEMS					
Residual heat indicator	*	*	*	*	*
Safety blocking	*	*	*	*	*
Automatic safety disconnection	*	*	*	*	*
COOKING ZONES					
Front left	Ø 145 1400-1800 W	Ø 180-280 2500-3700 W	Ø 180 1500/2200 W	HL ø 120/190 800/1900 W	Flex 235 x 180 1850-2200W
Front middle	-	Ø 145 1400-1800 W	-	-	-
Front right	Ø 180 1850-2500 W	Ø 210 2.300-3.200 W	Ø 240 2000/3000 W	Ø 210 1500-2000 W	Flex 235 x 180 1850-2200W
Rear left	Ø 210 2.300-3.200 W	-	-	-	Flex 235 x 180 1850-2200W
Rear middle	-	-	-	-	-
Rear right	Ø 180 1850-2500 W	-	-	-	Flex 235 x 180 1850-2200W
HOB PERFORMANCE (ACCORDING TO EU 66/2014 REGULATION)					
ø19/30 cm ECElectric cooking-Induction, Wh/Kg	172	-	-	-	-
ø28 cm ECElectric cooking-Induction, Wh/Kg	-	-	-	-	-
ø18/28 cm ECElectric cooking-Induction, Wh/Kg	-	172	-	-	-
ø26 cm ECElectric cooking-Induction, Wh/Kg	-	-	-	-	-
ø21 cm ECElectric cooking-Induction, Wh/Kg	178	178	180	183	-
ø18 cm ECElectric cooking-Induction, Wh/Kg	184	-	-	-	-
ø14,5 cm ECElectric cooking-Induction, Wh/Kg	202	202	198	-	-
27 x 18 cm ECElectric cooking-Induction, Wh/Kg	-	-	-	-	-
23,5 x 19 cm ECElectric cooking-Induction, Wh/Kg	-	-	-	-	Area Flex=190,3 Individual= 178
ø12/19 cm ECElectric cooking-Radiant heater, Wh/Kg	-	-	-	190	-
Energy consumption for the whole hob, Wh/Kg	184	184	189	187	190
EXTERNAL DIMENSIONS					
Width, mm	800	800	730	730	600
Depth, mm	510	400	430	430	510
BUILT-IN DIMENSIONS					
Width, mm	750	780	695	695	560
Depth, mm	490	380	360	360	490
ELECTRICAL FEATURES					
Voltage, V	230	230	230	230	230
Frequency, HZ	50/60	50/60	50/60	50/60	50/60
Maximum connection rating, W	7.400	7.400	3.500	3.800	7.400
Cable connection length, cm	110	110	110	120	110

MODEL	IZF 6420	IRS 641 WHITE	IR/IT/IZ 6420	IZ/IB 6415
FEATURES				
Type	Induction	Induction	Induction	Induction
Touch Control	Multislider PRO	Slider	Multislider PRO	Multislider
Space Induction	SPACE	-	-	-
Frame	Frontal Bevelled	Bevelled	IT=New metal frame JR=Bevelled IZ=Front bevelled	IZ=Front bevelled IB=Frameless
Cooking time programmer	•	•	•	•
Synchro function	-	-	•	-
Power Plus function	•	-	•	-
Power function	•	•	•	•
Stop&Go function	•	-	•	•
Pan optimization system	•	•	•	-
Power management function	•	-	•	•
Mute Function	•	-	•	•
Pan detector	•	•	•	•
Low-temp function	-	•	-	-
ICOOKING DIRECT FUNCTIONS				
iQuickBoiling	•	-	•	-
Simmering	•	-	•	-
Melting	•	-	•	-
Keep Warm	•	-	•	-
SAFETY SYSTEMS				
Residual heat indicator	•	•	•	•
Safety blocking	•	•	•	•
Automatic safety disconnection	•	•	•	•
COOKING ZONES				
Front left	Ø 145 1400-1800 W	Ø 145 1250/1800 W	Ø 145 1400-1800 W	Ø 145 1200-1500 W
Front middle	-	-	-	-
Front right	Flex 235 x 180 1850-2200W Ø 210	Ø 180 1750/2300W Ø 210	Ø 180 1850-2500 W Ø 210	Ø 180 1700-2100 W Ø 210
Rear left	2.300-3.200 W Ø 210	2250/3000 W Ø 210	2.300-3.200 W Ø 210	2.000-2.300 W Ø 210
Rear middle	-	-	-	-
Rear right	Flex 235 x 180 1850-2200W	Ø 180 1750-2300W	Ø 180 1850-2500 W	Ø 145 1200-1500 W
HOB PERFORMANCE (ACCORDING TO EU 66/2014 REGULATION)				
ø19/30 cm ECElectric cooking-Induction, Wh/Kg	-	-	-	-
ø28 cm ECElectric cooking-Induction, Wh/Kg	-	-	-	-
ø18/28 cm ECElectric cooking-Induction, Wh/Kg	-	-	-	-
ø26 cm ECElectric cooking-Induction, Wh/Kg	-	-	-	-
ø21 cm ECElectric cooking-Induction, Wh/Kg	178	180	178	177
ø18 cm ECElectric cooking-Induction, Wh/Kg	-	185	189	179
ø14,5 cm ECElectric cooking-Induction, Wh/Kg	202	198	202	183
27 x 18 cm ECElectric cooking-Induction, Wh/Kg	-	-	-	-
23,5 x 19 cm ECElectric cooking-Induction, Wh/Kg	Area Flex=190,3 Individual= 178	-	-	-
ø12/19 cm ECElectric cooking-Radiant heater, Wh/Kg	-	-	-	-
Energy consumption for the whole hob, Wh/Kg	190	190	190	181
EXTERNAL DIMENSIONS				
Width, mm	600	600	600	600
Depth, mm	510	510	510	510
BUILT-IN DIMENSIONS				
Width, mm	560	560	560	560
Depth, mm	490	490	490	490
ELECTRICAL FEATURES				
Voltage, V	230	230	230	230
Frequency, HZ	50/60	50/60	50/60	50/60
Maximum connection rating, W	7.400	7.000	7.400	7.200
Cable connection lenght, cm	110	110	110	110

MODEL	IBR 6040	IZF/ITF 6320	IRS 631 WHITE	IT/IZ/IR 6320
FEATURES				
Type	Induction	Induction	Induction	Induction
Touch Control	•	Multislider PRO	Slider	Multislider PRO
Space Induction	-	SPACE	-	-
Frame	Frameless	ITF=New metal frame IZF=Front bevelled	Bevelled	IT=New metal frame IR=Bevelled IZ=Front bevelled
Cooking time programmer	•	•	•	•
Synchro function	-	-	-	-
Power Plus function	-	•	-	•
Power function	•	•	•	•
Stop&Go function	-	•	-	•
Pan optimization system	-	•	-	•
Power management function	•	•	-	•
Mute Function	-	-	-	•
Pan detector	•	•	•	•
Low-temp function	•	-	•	-
ICOOKING DIRECT FUNCTIONS				
iQuickBoiling	-	-	-	•
Simmering	-	•	-	•
Melting	-	•	-	•
Keep Warm	-	•	-	•
SAFETY SYSTEMS				
Residual heat indicator	•	•	•	•
Safety blocking	•	•	•	•
Automatic safety disconnection	•	•	•	•
COOKING ZONES				
Front left	Ø 145 1400-1500 W	Flex 235 x 180 1850-2200W	Ø 145 1250/1800 W	Ø 145 1400-1800 W
Front middle	-	-	-	-
Front right	Ø 180 1800-2100 W	Ø 180/280 2500-3700 W	Ø 180/280 2400/3200 W	Ø 190/300 2500-3700 W
Rear left	Ø 210 2.200-2.300 W	Flex 235 x 180 1850-2200W	Ø 210 2250/3000 W	Ø 210 2.300-3.200 W
Rear middle	-	-	-	-
Rear right	Ø 145 1400-1500 W	-	-	-
HOB PERFORMANCE (ACCORDING TO EU 66/2014 REGULATION)				
ø19/30 cm ECElectric cooking-Induction, Wh/Kg	-	-	-	172
ø28 cm ECElectric cooking-Induction, Wh/Kg	-	-	-	-
ø18/28 cm ECElectric cooking-Induction, Wh/Kg	-	172	155	-
ø26 cm ECElectric cooking-Induction, Wh/Kg	-	-	-	-
ø21 cm ECElectric cooking-Induction, Wh/Kg	177	-	180	178
ø18 cm ECElectric cooking-Induction, Wh/Kg	179	-	-	-
ø14,5 cm ECElectric cooking-Induction, Wh/Kg	183	-	198	202
27 x 18 cm ECElectric cooking-Induction, Wh/Kg	-	-	-	-
23,5 x 19 cm ECElectric cooking-Induction, Wh/Kg	-	Area Flex=190,3 Individual= 178	-	-
ø12/19 cm ECElectric cooking-Radiant heater, Wh/Kg	-	-	-	-
Energy consumption for the whole hob, Wh/Kg	181	181	178	184
EXTERNAL DIMENSIONS				
Width, mm	600	600	600	605
Depth, mm	510	510	510	515
BUILT-IN DIMENSIONS				
Width, mm	560	560	560	560
Depth, mm	490	490	490	490
ELECTRICAL FEATURES				
Voltage, V	230	230	230	230
Frequency, HZ	50/60	50/60	50/60	50/60
Maximum connection rating, W	7.200	7.400	6.700	7.400
Cable connection lenght, cm	110	110	110	110

MODEL	IZ/IB 6315	IB 6310	IRC 6300	IR 5300
FEATURES				
Type	Induction	Induction	Induction	Induction
Touch Control	Multislider	Multislider	•	•
Space Induction	-	-	-	-
Frame	IZ=Front bevelled IB=Frameless	Frameless	Diamond Bevelled	Bevelled
Cooking time programmer	•	•	•	•
Synchro function	-	-	-	-
Power Plus function	-	-	•	•
Power function	•	•	•	•
Stop&Go function	•	•	-	-
Pan optimization system	-	-	•	•
Power management function	•	•	•	•
Mute Function	•	•	•	•
Pan detector	•	•	•	•
Low-temp function	-	-	•	•
ICOOKING DIRECT FUNCTIONS				
iQuickBoiling	-	-	-	-
Simmering	-	-	-	-
Melting	-	-	-	-
Keep Warm	-	-	-	-
SAFETY SYSTEMS				
Residual heat indicator	•	•	•	•
Safety blocking	•	•	•	•
Automatic safety disconnection	•	•	•	•
COOKING ZONES				
Front left	Ø 145 1200-1500 W	Ø 145 1200-1500 W	Ø 145 1400-1800 W	Ø 145 1400-1800 W
Front middle	-	-	-	-
Front right	Ø 180/280 2.500-3.600 W	Ø 260 2.000-2.300 W	Ø 180-280 2500-3700 W	Ø 180-280 2500-3700 W
Rear left	Ø 180 1700-2100 W	Ø 180 1700-2100 W	Ø 180 1850-2500 W	Ø 145 1400-1800 W
Rear middle	-	-	-	-
Rear right	-	-	-	-
HOB PERFORMANCE (ACCORDING TO EU 66/2014 REGULATION)				
Ø19/30 cm ECElectric cooking-Induction, Wh/Kg	-	-	-	-
Ø28 cm ECElectric cooking-Induction, Wh/Kg	-	-	-	-
Ø18/28 cm ECElectric cooking-Induction, Wh/Kg	171	-	155	155
Ø26 cm ECElectric cooking-Induction, Wh/Kg	-	184	-	-
Ø21 cm ECElectric cooking-Induction, Wh/Kg	-	-	-	-
Ø18 cm ECElectric cooking-Induction, Wh/Kg	179	179	185	-
Ø14,5 cm ECElectric cooking-Induction, Wh/Kg	183	183	198	198
27 x 18 cm ECElectric cooking-Induction, Wh/Kg	-	-	-	-
23,5 x 19 cm ECElectric cooking-Induction, Wh/Kg	-	-	-	-
Ø12/19 cm ECElectric cooking-Radiant heater, Wh/Kg	-	-	-	-
Energy consumption for the whole hob, Wh/Kg	178	182	179	184
EXTERNAL DIMENSIONS				
Width, mm	600	600	590	600
Depth, mm	510	510	510	435
BUILT-IN DIMENSIONS				
Width, mm	560	560	570	580
Depth, mm	490	490	492	415
ELECTRICAL FEATURES				
Voltage, V	230	230	230	230
Frequency, HZ	50/60	50/60	50/60	50/60
Maximum connection rating, W	7.200	5.900	7.400	7.300
Cable connection length, cm	110	110	110	110

MODEL	VR TC 95	TR 951	TR 941 HZ	TR 841	TR/TB 842
FEATURES					
Type	High light	High light	High light	High light	High light
Touch Control	•	•	•	•	•
Frame	Bevelled	Bevelled	Bevelled	Bevelled	TR=Bevelled TB=Frameless
Metallic k-bs	-	-	-	-	-
Cooking time programmer	•	•	•	•	•
Stop&Go function	•	•	•	•	•
Burst of cooking function	•	•	•	•	•
SAFETY SYSTEMS					
Residual heat indicator	•	•	•	•	•
Safety blocking	•	•	•	•	•
Automatic safety disconnection	•	•	•	•	•
COOKING ZONES					
Front left	Ø 120/180/210 800/1600/2300 W	Ø 145 1200 W	Ø 120/180/210 800/1600/2300 W	Ø 145/210/270 1050/1950/2700 W	Ø 120/180/210 800/1600/2300 W
Front middle	Ø 120/180 700/1700 W	Ø 145/210/270 1050/1950/2700 W	Ø 145 1200 W	-	-
Front right	Ø 180 1800 W	Ø 180 1800 W	Ø 120/180 700/1700 W	Ø 145 1200 W	Ø 180 1800 W
Rear left	-	Ø 120/180 700/1700 W	-	Ø 145 1200 W	Ø 145 1200 W
Rear middle	Ø 180 1800 W	-	Ø 145 1200 W	-	-
Rear right	-	Ø 160 1500 W	-	Ø 120/180 700/1700 W	Oval zone 170x265 mm.
HOB PERFORMANCE (ACCORDING TO EU 66/2014 REGULATION)					
Ø14,5/21/27 cm ECElectric cooking-Radiant heater, Wh/Kg	-	189,47	-	189,47	-
Ø12/18/21 cm ECElectric cooking-Radiant heater, Wh/Kg	189,47	-	189,47	-	189,47
Ø21/27 cm ECElectric cooking-Radiant heater, Wh/Kg	-	-	-	-	-
Ø18/23 cm ECElectric cooking-Radiant heater, Wh/Kg	-	-	-	-	-
Ø18/21 cm ECElectric cooking-Radiant heater, Wh/Kg	-	-	-	-	-
Ø12/18 cm ECElectric cooking-Radiant heater, Wh/Kg	192,33	196,34	192,33	192,33	-
Ø21 cm ECElectric cooking-Radiant heater, Wh/Kg	-	-	-	-	-
Ø18 cm ECElectric cooking-Radiant heater, Wh/Kg	188,33	187,33	-	-	188,33
Ø16 cm ECElectric cooking-Radiant heater, Wh/Kg	-	187,67	-	-	-
Ø14,5 cm ECElectric cooking-Radiant heater, Wh/Kg	-	189,32	188,02	188,02	188,02
Ø10 cm ECElectric cooking-Radiant heater, Wh/Kg	-	-	-	-	-
Ø12/21 cm ECElectric cooking-Radiant heater, Wh/Kg	-	-	-	-	-
Oval 17x27 cm ECElectric cooking-Radiant heater, Wh/Kg	-	-	-	-	188,67
Energy consumption for the whole hob, Wh/Kg	189,61	190,02	189,46	189,46	188,62
EXTERNAL DIMENSIONS					
Width, mm	950	900	900	800	800
Depth, mm	520	510	400	510	510
BUILT-IN DIMENSIONS					
Width, mm	930	860	860	750	750
Depth, mm	500	490	380	490	490
Height	55	63	63	63	63
ELECTRICAL FEATURES					
Voltage, V	230	230	230	230	230
Frequency, HZ	50/60	50/60	50/60	50/60	50/60
Maximum connection rating,	7.600	8.900	6.400	6.800	7.500
Cable connection length, cm	90	110	110	110	110

MODEL	TR 831 HZ	TRS 645	TR/TT/TB 642	TR/TT/TZ 6420	TR/TT/TZ/TB 6415
FEATURES					
Type	High light	High light	High light	High light	High light
Touch Control	•	•	•	•	•
Frame	Bevelled	Bevelled	TT= SS TR=Bevelled TB=Frameless	TT=New metal frame TR=Bevelled TZ=Front bevelled	TT=New metal frame TR=Bevelled TZ=Front bevelled TB=Frameless
Metallic k-bs	-	-	-	-	-
Cooking time programmer	•	•	•	•	•
Stop&Go function	•	-	•	-	-
Burst of cooking function	•	•	•	•	•
SAFETY SYSTEMS					
Residual heat indicator	•	•	•	•	•
Safety blocking	•	•	•	•	•
Automatic safety disconnection	•	•	•	•	•
COOKING ZONES					
Front left	Ø 145/210/270 1050/1950/2700 W	Ø 145 1200 W	Ø 120/180/210, 800/1600/2300 W	Ø 180 /210 1400/2000 W	Ø 210 2100 W
Front middle	Ø 145 1200 W	-	-	Ø 180 1800 W	Ø 180 1800 W
Front right	Ø 180 1800 W	Ø 145 1200 W	Ø 145 1200 W	-	-
Rear left	-	Ø 180/210 1400/2000 W	Ø 145 1200 W	Ø 145 1200 W	Ø 145 1200 W
Rear middle	-	-	-	Ø 145 1200 W	Ø 145 1200 W
Rear right	-	Ø 180 1800 W	Oval zone 170x265 mm.	-	-
HOB PERFORMANCE (ACCORDING TO EU 66/2014 REGULATION)					
Ø14,5/21/27 cm ECElectric cooking–Radiant heater, Wh/Kg	189,47	-	-	-	-
Ø12/18/21 cm ECElectric cooking–Radiant heater, Wh/Kg	-	-	189,47	-	-
Ø21/27 cm ECElectric cooking–Radiant heater, Wh/Kg	-	-	-	-	-
Ø18/23 cm ECElectric cooking–Radiant heater, Wh/Kg	-	-	-	-	-
Ø18/21 cm ECElectric cooking–Radiant heater, Wh/Kg	-	189,51	-	189,51	-
Ø12/18 cm ECElectric cooking–Radiant heater, Wh/Kg	-	-	-	-	-
Ø21 cm ECElectric cooking–Radiant heater, Wh/Kg	-	-	-	-	190
Ø18 cm ECElectric cooking–Radiant heater, Wh/Kg	187,33	187,33	-	187,33	187,33
Ø16 cm ECElectric cooking–Radiant heater, Wh/Kg	-	-	-	-	-
Ø14,5 cm ECElectric cooking–Radiant heater, Wh/Kg	189,32	189,32	188,02	189,32	189,32
Ø10 cm ECElectric cooking–Radiant heater, Wh/Kg	-	-	-	-	-
Ø12/21 cm ECElectric cooking–Radiant heater, Wh/Kg	-	-	-	-	-
Oval 17x27 cm ECElectric cooking–Radiant heater, Wh/Kg	-	-	188,67	-	-
Energy consumption for the whole hob, Wh/Kg	188,7	188,86	188,54	188,72	188,88
EXTERNAL DIMENSIONS					
Width, mm	800	600	600	600	600
Depth, mm	400	510	510	510	510
BUILT-IN DIMENSIONS					
Width, mm	780	560	560	560	560
Depth, mm	380	490	490	490	490
Height	63	63	63	63	63
ELECTRICAL FEATURES					
Voltage, V	230	230	230	230	230
Frequency, HZ	50/60	50/60	50/60	50/60	50/60
Maximum connection rating,	5.700	6.200	6.900	6.200	6.300
Cable connection lenght, cm	110	110	110	100	100

MODEL	TR 634	TBR 6420	TC 6400	VT CM	TRS 635
FEATURES					
Type	High light	High light	High light	High light	High light
Touch Control	•	•	•	-	Slider
Frame	Bevelled	Bevelled	Diamond Bevelled	Stainless Steel	Bevelled
Metallic k-bs	-	-	-	•	-
Cooking time programmer	-	•	•	-	•
Stop&Go function	-	-	-	-	-
Burst of cooking function	•	•	•	-	•
SAFETY SYSTEMS					
Residual heat indicator	•	•	•	•	•
Safety blocking	•	•	•	-	•
Automatic safety disconnection	•	•	•	-	•
COOKING ZONES					
Front left	Ø 100 600 W	Ø 180 /210 1400/2000 W	Ø 180 /210 1400/2000 W	Ø 180 1800 W	Ø 145 1200 W
Front middle	-	Ø 180 1800 W	Ø 180 1800 W	-	-
Front right	Ø 160 1500 W	-	-	Ø 145 1200 W	Ø 145/210/270 1050/1950/2700 W
Rear left	Ø 210/270 1500/2400 W	Ø 145 1200 W	Ø 145 1200 W	Ø 145 1200 W	Ø 180 1800 W
Rear middle	-	Ø 145 1200 W	Ø 160 1500 W	-	-
Rear right	Ø 145 1200 W	-	-	Ø 180 1800 W	-
HOB PERFORMANCE (ACCORDING TO EU 66/2014 REGULATION)					
Ø14,5/21/27 cm ECElectric cooking–Radiant heater, Wh/Kg	-	-	-	-	189,47
Ø12/18/21 cm ECElectric cooking–Radiant heater, Wh/Kg	-	-	-	-	-
Ø21/27 cm ECElectric cooking–Radiant heater, Wh/Kg	188,3	-	-	-	-
Ø18/23 cm ECElectric cooking–Radiant heater, Wh/Kg	-	-	-	-	-
Ø18/21 cm ECElectric cooking–Radiant heater, Wh/Kg	-	189,51	189,51	-	-
Ø12/18 cm ECElectric cooking–Radiant heater, Wh/Kg	-	-	-	-	-
Ø21 cm ECElectric cooking–Radiant heater, Wh/Kg	-	-	-	-	-
Ø18 cm ECElectric cooking–Radiant heater, Wh/Kg	-	187,33	187,33	187,33	187,33
Ø16 cm ECElectric cooking–Radiant heater, Wh/Kg	188	-	187,67	-	-
Ø14,5 cm ECElectric cooking–Radiant heater, Wh/Kg	188,02	189,32	189,32	189,32	189,32
Ø10 cm ECElectric cooking–Radiant heater, Wh/Kg	196,92	-	-	-	-
Ø12/21 cm ECElectric cooking–Radiant heater, Wh/Kg	-	-	-	-	-
Oval 17x27 cm ECElectric cooking–Radiant heater, Wh/Kg	-	-	-	-	-
Energy consumption for the whole hob, Wh/Kg	190,31	188,72	188,45	188,32	188,7
EXTERNAL DIMENSIONS					
Width, mm	600	600	590	600	600
Depth, mm	510	510	510	510	510
BUILT-IN DIMENSIONS					
Width, mm	560	560	570	580	560
Depth, mm	490	490	492	492	490
Height	63	63	63	60	63
ELECTRICAL FEATURES					
Voltage, V	230	230	230	230	230
Frequency, HZ	50/60	50/60	50/60	50/60	50/60
Maximum connection rating,	5.750	6.200	6.500	6.000	5.700
Cable connection lenght, cm	110	100	100	90	110

MODEL	TR/TT/TZ 6320	TR/TT/TZ/TB 6315	TB 6310	TR 5300
FEATURES				
Type	High light	High light	High light	High light
Touch Control	•	•	•	•
Frame	TT=New metal frame TR=Bevelled TZ=Front bevelled	TT=New metal frame TR=Bevelled TZ=Front bevelled TB=Frameless	Frameless	Bevelled
Metallic k-bs	-	-	-	-
Cooking time programmer	•	•	-	•
Stop&Go function	-	-	-	-
Burst of cooking function	•	•	-	•
SAFETY SYSTEMS				
Residual heat indicator	•	•	•	•
Safety blocking	•	•	•	•
Automatic safety disconnection	•	•	•	•
COOKING ZONES				
Front left	Ø 120/180 700-1700 W	Ø 180 1800 W	Ø 180 1800 W	Ø 120/180 1500/2400 W
Front middle	Ø 210/270 1800 / 2700 W	Ø 210/270 1500/2400 W	Ø 180/230 1500 / 2400 W	Ø 180/230 1500 / 2400 W
Front right	-	-	-	-
Rear left	Ø 145 1200 W	Ø 145 1200 W	Ø 145 1200 W	Ø 100 600 W
Rear middle	-	-	-	-
Rear right	-	-	-	-
HOB PERFORMANCE (ACCORDING TO EU 66/2014 REGULATION)				
Ø14,5/21/27 cm ECElectric cooking-Radiant heater, Wh/Kg	-	-	-	-
Ø12/18/21 cm ECElectric cooking-Radiant heater, Wh/Kg	-	-	-	-
Ø21/27 cm ECElectric cooking-Radiant heater, Wh/Kg	188,3	188,3	-	-
Ø18/23 cm ECElectric cooking-Radiant heater, Wh/Kg	-	-	189	189
Ø18/21 cm ECElectric cooking-Radiant heater, Wh/Kg	-	-	-	-
Ø12/18 cm ECElectric cooking-Radiant heater, Wh/Kg	196,34	-	-	196,34
Ø21 cm ECElectric cooking-Radiant heater, Wh/Kg	-	-	-	-
Ø18 cm ECElectric cooking-Radiant heater, Wh/Kg	-	187,33	187,33	-
Ø16 cm ECElectric cooking-Radiant heater, Wh/Kg	-	-	-	-
Ø14,5 cm ECElectric cooking-Radiant heater, Wh/Kg	189,32	189,32	189,32	-
Ø10 cm ECElectric cooking-Radiant heater, Wh/Kg	-	-	-	196,15
Ø12/21 cm ECElectric cooking-Radiant heater, Wh/Kg	-	-	-	-
Oval 17x27 cm ECElectric cooking-Radiant heater, Wh/Kg	-	-	-	-
Energy consumption for the whole hob, Wh/Kg	191,32	188,32	188,55	193,83
EXTERNAL DIMENSIONS				
Width, mm	600	600	600	600
Depth, mm	510	510	510	435
BUILT-IN DIMENSIONS				
Width, mm	560	560	560	580
Depth, mm	490	490	490	415
Height	63	63	63	63
ELECTRICAL FEATURES				
Voltage, V	230	230	230	230
Frequency, HZ	50/60	50/60	50/60	50/60
Maximum connection rating,	5.600	5.400	5.100	4.750
Cable connection lenght, cm	110	110	100	110

MODEL	TB 5303	VTC R/T/B 2DC E	VT N DC	VTC B
FEATURES				
Type	High light	High light	High light	High light
Touch Control	•	-	-	-
Frame	Frameless	TT= SS TR=Bevelled TB=Frameless	Stainless Steel	Stainless Steel
Metallic k-bs	-	-	-	-
Cooking time programmer	-	-	-	-
Stop&Go function	-	-	-	-
Burst of cooking function	•	-	-	-
SAFETY SYSTEMS				
Residual heat indicator	•	•	•	•
Safety blocking	•	-	-	-
Automatic safety disconnection	•	-	-	-
COOKING ZONES				
Front left	Ø 145 1200 W	Ø 120/210 700-2100 W	Ø 120/210 700-2100 W	Ø 210 2100 W
Front middle	Ø 210 2100 W	-	-	-
Front right	-	Ø 145 1200 W	Ø 180 1800 W	Ø 145 1200 W
Rear left	Ø 145 1200 W	Ø 145 1200 W	Ø 145 1200 W	Ø 145 1200 W
Rear middle	-	-	-	-
Rear right	-	Oval zone 170x265 mm.	Ø 180 1800 W	Ø 180 1800 W
HOB PERFORMANCE (ACCORDING TO EU 66/2014 REGULATION)				
Ø14,5/21/27 cm ECElectric cooking-Radiant heater, Wh/Kg	-	-	-	-
Ø12/18/21 cm ECElectric cooking-Radiant heater, Wh/Kg	-	-	-	-
Ø21/27 cm ECElectric cooking-Radiant heater, Wh/Kg	-	-	-	-
Ø18/23 cm ECElectric cooking-Radiant heater, Wh/Kg	-	-	-	-
Ø18/21 cm ECElectric cooking-Radiant heater, Wh/Kg	-	-	-	-
Ø12/18 cm ECElectric cooking-Radiant heater, Wh/Kg	-	-	-	-
Ø21 cm ECElectric cooking-Radiant heater, Wh/Kg	190	-	-	190
Ø18 cm ECElectric cooking-Radiant heater, Wh/Kg	-	-	187,33	187,33
Ø16 cm ECElectric cooking-Radiant heater, Wh/Kg	-	-	-	-
Ø14,5 cm ECElectric cooking-Radiant heater, Wh/Kg	189,32	188,02	189,32	189,32
Ø10 cm ECElectric cooking-Radiant heater, Wh/Kg	-	-	-	-
Ø12/21 cm ECElectric cooking-Radiant heater, Wh/Kg	-	196,34	196,34	-
Oval 17x27 cm ECElectric cooking-Radiant heater, Wh/Kg	-	188,67	-	-
Energy consumption for the whole hob, Wh/Kg	189,66	190,26	188,32	190,99
EXTERNAL DIMENSIONS				
Width, mm	600	600	590	600
Depth, mm	435	510	510	510
BUILT-IN DIMENSIONS				
Width, mm	580	560	570	580
Depth, mm	415	492	492	492
Height	63	115	63	115
ELECTRICAL FEATURES				
Voltage, V	230	230	230	230
Frequency, HZ	50/60	50/60	50/60	50/60
Maximum connection rating,	4.500	6.800	6.900	6.300
Cable connection lenght, cm	110	90	90	90

MODEL	IG 940 2G AI AL CI	IG 940 1G AI AL DR CI	IG 620 2G AI AL CI	IG 620 1G AI AL DR CI
EXTERNAL DIMENSIONS				
Width	880	880	600	600
Depth	505	505	505	505
BUILT-IN DIMENSIONS				
Width	860	860	560	560
Height	490	490	490	490
Depth (min.)	50	50	50	50
ELECTRICAL CONNECTION				
Power supply, 230 v	•	•	•	•
Frequency, Hz	50/60	50/60	50/60	50/60
Maximum nominal power, induction (kW)	7200	7200	3600	3600
Maximum nominal power, gas (kW)	3,8	5	3,8	5
Wire lenght cm.	120	120	120	120
GAS CONNECTION				
Maximum power kW	7,2	7,2	3,6	3,6
HEATING ELEMENTS				
Electric solid plate Ø 180/1500 W	–	–	–	–
Electric solid plate Ø 145/1500 W	–	–	–	–
Electric solid plate Ø 145/1000 W	–	–	–	–
Double ring burner, 5,0 kW	–	1	–	1
Double ring burner, 4,20 kW	–	–	–	–
Triple ring burner, 4,00 kW	–	–	–	–
Triple ring burner, 3,50 kW	–	–	–	–
Triple ring burner, 3,10 kW	–	–	–	–
Triple ring burner, 3,80 kW	–	–	–	–
Fast burner, 3,00 kW	–	–	–	–
Fast burner, 2,80 kW	1	–	1	–
Fast burner, 2,70 kW	–	–	–	–
Semifast burner, 3,00 kW	–	–	–	–
Semifast burner, 1,75 kW	–	–	–	–
Semifast burner, 1,40 kW	–	–	–	–
Auxiliary burner, 1,00 kW	1	–	1	–
High light ø 180, 1800 W	–	–	–	–
High light ø 145, 1200 W	–	–	–	–
Induction zone Ø 210 mm: 1.500 W – Power 2.000 W	2	2	1	1
Induction zone Ø 145 mm: 1.200 W – Power 1.600 W	2	2	1	1
HOB PERFORMANCE (ACCORDING TO EU 66/2014 REGULATION)				
ø21 cm ECElectric cooking–Radiant heater, Wh/Kg	183,4	183,4	183,4	183,4
ø14,5 cm ECElectric cooking–Induction, Wh/Kg	176,4	176,4	176,4	176,4
Double ring burner EE Gas burner, %	–	61,6	–	61,6
Fast burner EE Gas burner, %	56	–	56	–
Auxiliary burner EE Gas burner, %	n.a.	–	n.a.	–
Energy consumption for the whole hob, Wh/Kg	179,9	179,9	179,9	179,9
Energy efficiency for the whole gas hob, %	56	61,6	56	61,6
FEATURES				
Knobs	•	•	•	•
Auto ignition	•	•	•	•
Power lamp indicator	–	–	–	–
Timer	•	•	•	•
Power Management	•	•	•	•
ACCESSORIES				
Enamelled grids	–	–	–	–
Cast iron grids	•	•	•	•
Individual grids	–	–	–	–
Grid accesory	–	–	–	–
Supplementary small recipient	–	–	–	–
SAFETY SYSTEMS				
Residual heat indicator	•	•	•	•
Automatic safety device	•	•	•	•
FINISHING				
Stainless steel frame	–	–	–	–
Bevelled glass	–	–	–	–
Frameless glass	•	•	•	•
Stainless steel	–	–	–	–
Enamelled Beige / Anthracite	–	–	–	–

MODEL	VR 90 4G AI AL TR	CGW LUX 90 TC 5G AI AL DR CI	CGW LUX 90 5G AI AL DR CI	CGW LUX 86 TC 3G AI AL 2TR CI	CGW LUX 86 2G 1P AI AL 2TR CI
EXTERNAL DIMENSIONS					
Width	900	870	870	860	860
Depth	510	512	512	450	450
BUILT-IN DIMENSIONS					
Width	880	833	833	710	710
Height	490	475	475	410	410
Depth (min.)	55	50	50	54	54
ELECTRICAL CONNECTION					
Power supply, 230 v	•	•	•	•	•
Frequency, Hz	50/60	50/60	50/60	50/60	50/60
Maximum nominal power (kW)	0,6	0,6	0,6	0,6	0,6
GAS CONNECTION					
Maximum power kW	9,25	11,15	11,55	10,15	8,00
HEATING ELEMENTS					
Electric solid plate Ø 145/1500 W	–	–	–	–	1
Double ring burner, 5,0 kW	–	–	1	–	–
Double ring burner, 4,20 kW	–	1	–	2	–
Triple ring burner, 4,00 kW	–	–	–	–	2
Triple ring burner, 3,50 kW	1	–	–	–	–
Fast burner, 3,00 Kw	1	–	–	–	–
Fast burner, 2,80 kW	–	1	1	–	–
Semifast burner, 1,75 kW	1	1	1	1	–
Semifast burner, 1,40 kW	–	1	1	–	–
Auxiliary burner, 1,00 kW	1	1	1	–	–
HOB PERFORMANCE (ACCORDING TO EU 66/2014 REGULATION)					
ø21 cm ECElectric cooking–Induction, Wh/Kg	–	–	–	–	–
ø14,5 cm ECElectric cooking–Induction, Wh/Kg	–	–	–	–	–
ø18 cm ECElectric cooking–Radiant heater, Wh/Kg	–	–	–	–	–
ø14,5 cm ECElectric cooking–Radiant heater, Wh/Kg	–	–	–	–	–
17 x 26,5 cm ECElectric cooking–Radiant heater, Wh/Kg	–	–	–	–	–
Ø 145 solid plate ECElectric cooking–plate heater, Wh/Kg	–	–	–	–	198,1
Triple ring burner EE Gas burner, %	53	–	–	54,9/54,9	55,3/55,3
Double ring burner EE Gas burner, %	–	52,2	61,6	–	–
Fast burner EE Gas burner, %	58	59,8	59,8	–	–
Semi-fast burner EE Gas burner, %	58	55	56,2	53,9	–
Semi-fast reduced burner EE Gas burner, %	–	60,3	57,8	–	–
Auxiliary burner EE Gas burner, %	n.a.	n.a.	n.a.	n.a.	n.a.
Energy consumption for the whole hob, Wh/Kg	–	–	–	–	198,1
Energy efficiency for the whole gas hob, %	56,3	56,8	58,9	54,6	55,3
FEATURES					
Knobs	•	–	•	–	•
Auto ignition	•	•	•	•	•
Power lamp indicator	–	–	–	–	•
ACCESSORIES					
Enamelled grids	–	–	–	–	–
Cast iron grids	•	•	•	•	•
Individual grids	•	–	–	•	•
Grid accesory	•	•	•	•	•
Supplementary small recipient	–	–	–	–	–
SAFETY SYSTEMS					
Residual heat indicator	–	–	–	–	•
Automatic safety device	•	•	•	•	•
FINISHING					
Stainless steel frame	–	–	–	–	–
Bevelled glass	•	–	–	•	–
Frameless glass	–	•	•	–	•
Stainless steel	–	–	–	–	–
Enamelled Beige / Anthracite	–	–	–	–	–

MODEL	CGW LUX 86 TC 2G AI AL 2TR CI	CGW LUX 86 2G AI AL 2TR CI	CGW LUX 78 2G AI AL 2TR CI	CGW LUX 78 2G 1P AI AL 2TR CI	CGW LUX 70 5G AI AL TR CI
EXTERNAL DIMENSIONS					
Width	860	860	780	780	710
Depth	450	450	450	450	512
BUILT-IN DIMENSIONS					
Width	710	710	710	710	570
Height	410	410	410	410	480
Depth (min.)	54	54	54	54	50
ELECTRICAL CONNECTION					
Power supply, 230 v	•	•	•	•	•
Frequency, Hz	50/60	50/60	50/60	50/60	50/60
Maximum nominal power (kW)	0,6	0,6	0,6	1500	0,6
GAS CONNECTION					
Maximum power kW	8,40	10,00	8,00	8,00	10,85
HEATING ELEMENTS					
Electric solid plate Ø 145/1500 W	–	–	–	1	–
Double ring burner, 5,0 kW	–	2	–	–	–
Double ring burner, 4,20 kW	2	–	–	–	–
Triple ring burner, 4,00 kW	–	–	2	2	1
Triple ring burner, 3,50 kW	–	–	–	–	–
Fast burner, 3,00 Kw	–	–	–	–	–
Fast burner, 2,80 kW	–	–	–	–	1
Semifast burner, 1,75 kW	–	–	–	–	1
Semifast burner, 1,40 kW	–	–	–	–	1
Auxiliary burner, 1,00 kW	–	–	–	–	1
HOB PERFORMANCE (ACCORDING TO EU 66/2014 REGULATION)					
ø21 cm ECElectric cooking–Induction, Wh/Kg	–	–	–	–	–
ø14,5 cm ECElectric cooking–Induction, Wh/Kg	–	–	–	–	–
ø18 cm ECElectric cooking–Radiant heater, Wh/Kg	–	–	–	–	–
ø14,5 cm ECElectric cooking–Radiant heater, Wh/Kg	–	–	–	–	–
17 x 26,5 cm ECElectric cooking–Radiant heater, Wh/Kg	–	–	–	–	–
Ø 145 solid plate ECElectric cooking–plate heater, Wh/Kg	–	–	–	198,1	–
Triple ring burner EE Gas burner, %	54,9/54,9	55,3/55,3	55,3/55,3	55,3/55,3	54,3
Double ring burner EE Gas burner, %	–	–	–	–	–
Fast burner EE Gas burner, %	–	–	–	–	59,8
Semi-fast burner EE Gas burner, %	–	–	–	–	56,2
Semi-fast reduced burner EE Gas burner, %	–	–	–	–	57,8
Auxiliary burner EE Gas burner, %	n.a.	n.a.	n.a.	n.a.	n.a.
Energy consumption for the whole hob, Wh/Kg	–	–	–	198,1	n.a.
Energy efficiency for the whole gas hob, %	54,9	55,3	55,3	55,3	57,0
FEATURES					
Knobs	–	•	•	•	•
Auto ignition	•	•	•	•	•
Power lamp indicator	–	–	–	•	–
ACCESSORIES					
Enamelled grids	–	–	–	–	–
Cast iron grids	•	•	•	•	•
Individual grids	•	•	•	•	–
Grid accesory	•	•	•	•	•
Supplementary small recipient	–	–	–	–	–
SAFETY SYSTEMS					
Residual heat indicator	–	–	–	•	–
Automatic safety device	•	•	•	•	•
FINISHING					
Stainless steel frame	–	–	–	–	–
Bevelled glass	•	•	–	–	–
Frameless glass	–	–	•	•	•
Stainless steel	–	–	–	–	–
Enamelled Beige / Anthracite	–	–	–	–	–

MODEL	CGW LUX 70 5G AI AL CI	CGW LUX 70 4G AI AL CI	CGW LUX 60 TC 4G AI AL CI	CGW LUX 60 4G AI AL TR CI	CGW LUX 60 4G AI AL CI
EXTERNAL DIMENSIONS					
Width	710	710	610	610	610
Depth	512	512	512	512	512
BUILT-IN DIMENSIONS					
Width	570	570	570	570	570
Height	480	480	480	480	480
Depth (min.)	50	50	50	50	50
ELECTRICAL CONNECTION					
Power supply, 230 v	•	•	•	•	•
Frequency, Hz	50/60	50/60	50/60	50/60	50/60
Maximum nominal power (kW)	0,6	0,6	0,6	0,6	0,6
GAS CONNECTION					
Maximum power kW	9,65	6,85	6,95	9,55	6,95
HEATING ELEMENTS					
Electric solid plate Ø 145/1500 W	–	–	–	–	–
Double ring burner, 5,0 kW	–	–	–	–	–
Double ring burner, 4,20 kW	–	–	–	–	–
Triple ring burner, 4,00 kW	–	–	–	1	–
Triple ring burner, 3,50 kW	–	–	–	–	–
Fast burner, 3,00 Kw	–	–	–	–	–
Fast burner, 2,80 kW	2	1	1	1	1
Semifast burner, 1,75 kW	1	1	1	1	1
Semifast burner, 1,40 kW	1	1	1	–	1
Auxiliary burner, 1,00 kW	1	1	1	1	1
HOB PERFORMANCE (ACCORDING TO EU 66/2014 REGULATION)					
ø21 cm ECElectric cooking–Induction, Wh/Kg	–	–	–	–	–
ø14,5 cm ECElectric cooking–Induction, Wh/Kg	–	–	–	–	–
ø18 cm ECElectric cooking–Radiant heater, Wh/Kg	–	–	–	–	–
ø14,5 cm ECElectric cooking–Radiant heater, Wh/Kg	–	–	–	–	–
17 x 26,5 cm ECElectric cooking–Radiant heater, Wh/Kg	–	–	–	–	–
Ø 145 solid plate ECElectric cooking–plate heater, Wh/Kg	–	–	–	–	–
Triple ring burner EE Gas burner, %	–	–	–	54,3	–
Double ring burner EE Gas burner, %	–	–	52,2	–	–
Fast burner EE Gas burner, %	59,8/56,0	56	59,8	59,8	59,8
Semi-fast burner EE Gas burner, %	56,2	56,2	55	56,2	56,2
Semi-fast reduced burner EE Gas burner, %	57,8	57,8	60,3	–	57,8
Auxiliary burner EE Gas burner, %	n.a.	n.a.	n.a.	n.a.	n.a.
Energy consumption for the whole hob, Wh/Kg	n.a.	n.a.	n.a.	n.a.	n.a.
Energy efficiency for the whole gas hob, %	57,5	56,7	56,8	56,8	57,9
FEATURES					
Knobs	•	•	–	•	•
Auto ignition	•	•	•	•	•
Power lamp indicator	–	–	–	–	–
ACCESSORIES					
Enamelled grids	–	–	–	–	–
Cast iron grids	•	•	•	•	•
Individual grids	–	–	–	–	–
Grid accesory	–	–	–	•	–
Supplementary small recipient	–	–	–	–	–
SAFETY SYSTEMS					
Residual heat indicator	–	–	–	–	–
Automatic safety device	•	•	•	•	•
FINISHING					
Stainless steel frame	–	–	–	–	–
Bevelled glass	–	–	–	–	–
Frameless glass	•	•	•	•	•
Stainless steel	–	–	–	–	–
Enamelled Beige / Anthracite	–	–	–	–	–

MODEL	CGW LUX 60 3G AI AL TR CI	HF LUX 60 4G AI AL	HF LUX 60 4G AI AL WHITE	HF LUX 60 3G AI AL TR CI	HF LUX 50 4G AI AL
EXTERNAL DIMENSIONS					
Width	610	580	580	580	600
Depth	512	500	500	500	435
BUILT-IN DIMENSIONS					
Width	570	560	560	560	580
Height	480	480	480	480	415
Depth (min.)	50	35	35	35	35
ELECTRICAL CONNECTION					
Power supply, 230 v	•	•	•	•	•
Frequency, Hz	50/60	50/60	50/60	50/60	50
Maximum nominal power (kW)	0,6	1,1	1,1	0,6	0,6
GAS CONNECTION					
Maximum power kW	7,80	7,50	7,50	6,25	6,80
HEATING ELEMENTS					
Electric solid plate Ø 145/1500 W	–	–	–	–	–
Double ring burner, 5,0 kW	–	–	–	–	–
Double ring burner, 4,20 kW	–	–	–	–	–
Triple ring burner, 4,00 kW	1	–	–	–	–
Triple ring burner, 3,50 kW	–	–	–	1	–
Fast burner, 3,00 Kw	–	1	1	–	1
Fast burner, 2,80 kW	1	–	–	–	–
Semifast burner, 1,75 kW	–	–	2	1	2
Semifast burner, 1,40 kW	–	–	–	–	–
Auxiliary burner, 1,00 kW	1	1	1	1	1
HOB PERFORMANCE (ACCORDING TO EU 66/2014 REGULATION)					
ø21 cm ECElectric cooking–Induction, Wh/Kg	–	–	–	–	–
ø14,5 cm ECElectric cooking–Induction, Wh/Kg	–	–	–	–	–
ø18 cm ECElectric cooking–Radiant heater, Wh/Kg	–	–	–	–	–
ø14,5 cm ECElectric cooking–Radiant heater, Wh/Kg	–	–	–	–	–
17 x 26,5 cm ECElectric cooking–Radiant heater, Wh/Kg	–	–	–	–	–
Ø 145 solid plate ECElectric cooking–plate heater, Wh/Kg	–	–	–	–	–
Triple ring burner EE Gas burner, %	54,3	–	–	–	–
Double ring burner EE Gas burner, %	–	–	–	–	–
Fast burner EE Gas burner, %	59,8	58,8	58,7	58,8	58,8
Semi-fast burner EE Gas burner, %	–	56,8	56,8	56,8	56,8
Semi-fast reduced burner EE Gas burner, %	–	n.a.	–	–	–
Auxiliary burner EE Gas burner, %	n.a.	n.a.	n.a.	n.a.	n.a.
Energy consumption for the whole hob, Wh/Kg	n.a.	n.a.	n.a.	n.a.	n.a.
Energy efficiency for the whole gas hob, %	57,0	57,8	57,4	57,8	57,8
FEATURES					
Knobs	•	•	•	•	•
Auto ignition	•	•	•	•	•
Power lamp indicator	–	–	–	–	–
ACCESSORIES					
Enamelled grids	–	•	–	–	•
Cast iron grids	•	–	•	•	–
Individual grids	–	•	•	•	•
Grid accessory	•	–	–	–	–
Supplementary small recipient	–	–	–	–	–
SAFETY SYSTEMS					
Residual heat indicator	–	–	–	–	–
Automatic safety device	•	•	•	•	•
FINISHING					
Stainless steel frame	–	–	–	–	–
Bevelled glass	–	–	–	–	–
Frameless glass	•	•	•	•	•
Stainless steel	–	–	–	–	–
Enamelled Beige / Anthracite	–	–	–	–	–

MODEL	HF LUX 50 3G 1P AI AL	HL LUX 60 4G AI AL	HL LUX 60 4G AI AL WHITE	ER 60 4G AI AL ANTHRACITE
EXTERNAL DIMENSIONS				
Width	600	580	580	580
Depth	435	500	500	500
BUILT-IN DIMENSIONS				
Width	580	560	560	553
Height	415	480	480	473
Depth (min.)	35	56	56	83
ELECTRICAL CONNECTION				
Power supply, 230 v	•	•	•	•
Frequency, Hz	50	50	50	50/60
Maximum nominal power (kW)	1500	1,1	1,1	1,1
GAS CONNECTION				
Maximum power kW	5,75	7,50	7,50	6,75
HEATING ELEMENTS				
Electric solid plate Ø 145/1500 W	1	–	–	–
Double ring burner, 5,0 kW	–	–	–	–
Double ring burner, 4,20 kW	–	–	–	–
Triple ring burner, 4,00 kW	–	–	–	–
Triple ring burner, 3,50 kW	–	–	–	–
Fast burner, 3,00 Kw	1	1	1	1
Fast burner, 2,80 kW	–	–	–	–
Semifast burner, 1,75 kW	1	2	2	1
Semifast burner, 1,40 kW	–	–	–	–
Auxiliary burner, 1,00 kW	1	1	1	2
HOB PERFORMANCE (ACCORDING TO EU 66/2014 REGULATION)				
ø21 cm ECElectric cooking–Induction, Wh/Kg	–	–	–	–
ø14,5 cm ECElectric cooking–Induction, Wh/Kg	–	–	–	–
ø18 cm ECElectric cooking–Radiant heater, Wh/Kg	–	–	–	–
ø14,5 cm ECElectric cooking–Radiant heater, Wh/Kg	–	–	–	–
17 x 26,5 cm ECElectric cooking–Radiant heater, Wh/Kg	–	–	–	–
Ø 145 solid plate ECElectric cooking–plate heater, Wh/Kg	198,1	–	–	–
Triple ring burner EE Gas burner, %	–	–	–	–
Double ring burner EE Gas burner, %	–	–	–	–
Fast burner EE Gas burner, %	58,7	58,7	58,7	58,7
Semi-fast burner EE Gas burner, %	56,8	56,8	56,8	56,8
Semi-fast reduced burner EE Gas burner, %	–	–	–	–
Auxiliary burner EE Gas burner, %	n.a.	n.a.	n.a.	n.a.
Energy consumption for the whole hob, Wh/Kg	195,0	n.a.	n.a.	n.a.
Energy efficiency for the whole gas hob, %	57,7	57,4	57,4	57,4
FEATURES				
Knobs	•	•	•	•
Auto ignition	•	•	•	•
Power lamp indicator	•	–	–	–
ACCESSORIES				
Enamelled grids	•	–	–	–
Cast iron grids	–	•	•	•
Individual grids	•	•	•	•
Grid accessory	–	–	–	–
Supplementary small recipient	–	–	–	–
SAFETY SYSTEMS				
Residual heat indicator	•	–	–	–
Automatic safety device	•	•	•	•
FINISHING				
Stainless steel frame	–	–	–	–
Bevelled glass	–	•	•	–
Frameless glass	•	–	–	–
Stainless steel	–	–	–	–
Enamelled Beige / Anthracite	–	–	–	–/•

MODEL	EW 90 5G AI AL TR CI	EW 90 5G AI AL TR CI BLACK	EW 60 4G AI AL CI	EW 60 4G AI AL CI BLACK	EFX 90 5G AI AL DR
EXTERNAL DIMENSIONS					
Width	870	870	590	590	860
Depth	520	520	520	520	510
BUILT-IN DIMENSIONS					
Width	845	845	565	565	833
Height	495	495	495	495	475
Depth (min.)	70	70	70	70	40
ELECTRICAL CONNECTION					
Power supply 230 v	•	•	•	•	•
Frequency Hz	50/60	50/60	50/60	50/60	50/60
Maximum nominal power	1,1	1,1	1,1	1,1	1,1
GAS CONNECTION					
Maximum power kW	10,05	10,05	6,95	6,95	11,5
HEATING ELEMENTS					
Electric solid plate Ø 145/1000 W	–	–	–	–	–
Double ring burner, 4,00 kW	–	–	–	–	1
Triple ring burner, 3,50 kW	–	–	–	–	–
Triple ring burner, 3,10 kW	1	1	–	–	–
Fast burner, 3,00 Kw	–	–	–	–	1
Fast burner, 2,80 kW	1	1	1	1	–
Semifast burner, 1,75 kW	1	1	1	1	2
Semifast burner, 1,40 kW	1	1	1	1	–
Auxiliary burner, 1,00 kW	1	1	1	1	1
High light ø 180, 1800 W	–	–	–	–	–
High light ø 145, 1200 W	–	–	–	–	–
HOB PERFORMANCE (ACCORDING TO EU 66/2014 REGULATION)					
ø21 cm ECElectric cooking–Induction, Wh/Kg	–	–	–	–	–
ø14,5 cm ECElectric cooking–Induction, Wh/Kg	–	–	–	–	–
ø18 cm ECElectric cooking–Radiant heater, Wh/Kg	–	–	–	–	–
ø14,5 cm ECElectric cooking–Radiant heater, Wh/Kg	–	–	–	–	–
17 x 26,5 cm ECElectric cooking–Radiant heater, Wh/Kg	–	–	–	–	–
Ø 145 solid plate ECElectric cooking–plate heater, Wh/Kg	–	–	–	–	–
Triple ring burner EE Gas burner, %	54	54	–	–	–
Double ring burner EE Gas burner, %	–	–	–	–	56,6
Fast burner EE Gas burner, %	60,2	60,2	60,2	60,2	58,8
Semi-fast burner EE Gas burner, %	55,9	55,9	55,9	55,9	58
Semi-fast reduced burner EE Gas burner, %	64	64	64	64	–
Auxiliary burner EE Gas burner, %	n.a.	n.a.	n.a.	n.a.	n.a.
Energy consumption for the whole hob, Wh/Kg	n.a.	n.a.	n.a.	n.a.	n.a.
Energy efficiency for the whole gas hob, %	58,5	58,5	60	60	57,9
FEATURES					
Knobs	•	•	•	•	•
Auto ignition	•	•	•	•	•
Power lamp indicator	–	–	–	–	–
ACCESSORIES					
Enamelled grids	–	–	–	–	–
Cast iron grids	•	•	•	•	•
Individual grids	–	–	–	–	–
Grid accesory	•	•	–	–	•
Supplementary small recipient	–	–	–	–	–
SAFETY SYSTEMS					
Residual heat indicator	–	–	–	–	–
Automatic safety device	•	•	•	•	•
FINISHING					
Stainless steel frame	–	–	–	–	–
Bevelled glass	–	–	–	–	–
Frameless glass	–	–	–	–	–
Stainless steel	•	•	•	•	•
Enamelled Beige / Anthracite	–	•	–	•	–

MODEL	EFX 90 5G AI AL DR LEFT	EFX 70 5G AI AL DR	EFX 60 4G AI AL DR	EFX 60 4G AI AL	EFX 60 2G 2H AI AL
EXTERNAL DIMENSIONS					
Width	860	750	600	600	600
Depth	510	510	510	510	510
BUILT-IN DIMENSIONS					
Width	833	553	553	553	553
Height	475	473	473	473	473
Depth (min.)	40	40	40	40	40
ELECTRICAL CONNECTION					
Power supply 230 v	•	•	•	•	•
Frequency Hz	50/60	50/60	50/60	50/60	50/60
Maximum nominal power	1,1	1,1	1,1	1,1	3000
GAS CONNECTION					
Maximum power kW	11,5	11,5	8,5	8,5	2,75
HEATING ELEMENTS					
Electric solid plate Ø 145/1000 W	–	–	–	–	–
Double ring burner, 4,00 kW	1	1	1	–	–
Triple ring burner, 3,50 kW	–	–	–	–	–
Triple ring burner, 3,10 kW	–	–	–	–	–
Fast burner, 3,00 Kw	1	1	–	1	–
Fast burner, 2,80 kW	–	–	–	–	–
Semifast burner, 1,75 kW	2	2	2	2	1
Semifast burner, 1,40 kW	–	–	–	–	–
Auxiliary burner, 1,00 kW	1	1	1	1	1
High light ø 180, 1800 W	–	–	–	–	1
High light ø 145, 1200 W	–	–	–	–	1
HOB PERFORMANCE (ACCORDING TO EU 66/2014 REGULATION)					
ø21 cm ECElectric cooking–Induction, Wh/Kg	–	–	–	–	–
ø14,5 cm ECElectric cooking–Induction, Wh/Kg	–	–	–	–	–
ø18 cm ECElectric cooking–Radiant heater, Wh/Kg	–	–	–	–	188,5
ø14,5 cm ECElectric cooking–Radiant heater, Wh/Kg	–	–	–	–	187,0
17 x 26,5 cm ECElectric cooking–Radiant heater, Wh/Kg	–	–	–	–	–
Ø 145 solid plate ECElectric cooking–plate heater, Wh/Kg	–	–	–	–	–
Triple ring burner EE Gas burner, %	–	–	–	–	–
Double ring burner EE Gas burner, %	56,6	56,6	56,6	–	–
Fast burner EE Gas burner, %	58,8	58,8	–	58,8	58,8
Semi-fast burner EE Gas burner, %	58,0	58,0	58,0	58,0	–
Semi-fast reduced burner EE Gas burner, %	–	–	–	–	–
Auxiliary burner EE Gas burner, %	n.a.	n.a.	n.a.	n.a.	n.a.
Energy consumption for the whole hob, Wh/Kg	n.a.	n.a.	n.a.	n.a.	n.a.
Energy efficiency for the whole gas hob, %	57,9	57,8	57,5	58,3	58,8
FEATURES					
Knobs	•	•	•	•	•
Auto ignition	•	•	•	•	•
Power lamp indicator	–	–	–	–	–
ACCESSORIES					
Enamelled grids	–	–	–	–	–
Cast iron grids	•	•	•	•	•
Individual grids	–	–	–	–	–
Grid accesory	•	•	•	•	–
Supplementary small recipient	–	–	–	–	–
SAFETY SYSTEMS					
Residual heat indicator	–	–	–	–	–
Automatic safety device	•	•	•	•	•
FINISHING					
Stainless steel frame	–	–	–	–	–
Bevelled glass	–	–	–	–	–
Frameless glass	–	–	–	–	–
Stainless steel	•	•	•	•	•
Enamelled Beige / Anthracite	–	–	–	–	–



TECHNICAL FEATURES

MODEL	EX 90.1 6G DR	EX 90.1 6G	EX 90.1 5G DR LEFT	EX 90.1 5G DR	EX 90.1 5G PC	EX 90.1 3G DR
EXTERNAL DIMENSIONS						
Width	860	860	860	860	860	860
Depth	500	500	500	500	500	500
BUILT-IN DIMENSIONS						
Width	833	833	833	833	833	833
Height	473	473	473	473	473	473
Depth (min.)	52	52	52	52	52	52
ELECTRICAL CONNECTION						
Power supply 230 v	*	*	*	*	*	*
Frequency Hz	50/60	50/60	50/60	50/60	50/60	50/60
Maximum nominal power	1,1	1,1	1,1	1,1	1,1	1,1
GAS CONNECTION						
Maximum power kW	13,05	10,80	12,05	11,30	10,10	8,55
HEATING ELEMENTS						
Electric solid plate Ø 145/1500 W	-	-	-	-	-	-
Electric solid plat Ø 145/1000 W	-	-	-	-	-	-
Double ring burner, 5,0 kW	-	-	-	-	-	-
Double ring burner, 4,00 kW	1	-	1	1	-	1
Triple ring burner, 4,00 kW	-	-	-	-	-	-
Triple ring burner, 3,50 kW	-	-	-	-	-	-
Triple ring burner, 3,10 kW	-	-	-	-	-	-
Triple ring burner, 3,80 kW	-	-	-	-	-	-
Fish burner, 2,80 kW	-	-	-	-	1	-
Fast burner, 3,00 Kw	-	-	-	-	-	-
Fast burner, 2,80 kW	1	1	1	1	1	1
Fast burner, 2,70 kW	-	-	-	-	-	-
Semifast burner, 1,75 kW	3	4	3	2	2	1
Semifast burner, 1,50 kW	-	-	-	-	-	-
Semifast burner, 1,40 kW	-	-	-	-	-	-
Auxiliary burner, 1,00 kW	1	1	-	1	1	-
High light ø 180, 1800 W	-	-	-	-	-	-
High light ø 145, 1200 W	-	-	-	-	-	-
HOB PERFORMANCE (ACCORDING TO EU 66/2014 REGULATION)						
ø21 cm ECElectric cooking-Induction, Wh/Kg	-	-	-	-	-	-
ø14,5 cm ECElectric cooking-Induction, Wh/Kg	-	-	-	-	-	-
ø18 cm ECElectric cooking-Radiant heater, Wh/Kg	-	-	-	-	-	-
ø14,5 cm ECElectric cooking-Radiant heater, Wh/Kg	-	-	-	-	-	-
17 x 26,5 cm ECElectric cooking-Radiant heater, Wh/Kg	-	-	-	-	-	-
Ø 145 solid plate ECElectric cooking-plate heater, Wh/Kg	-	-	-	-	-	-
Triple ring burner EE Gas burner, %	-	-	-	-	-	-
Double ring burner EE Gas burner, %	58,7	-	58,7	58,7	-	58,7
Fish burner EE Gas burner, %	-	-	-	-	58,9	-
Fast burner EE Gas burner, %	56,3	56,3	56,3	56,3	56,3	56,3
Semi-fast burner EE Gas burner, %	57,0	57,0	57,0	57,0	57,0	57,0
Semi-fast reduced burner EE Gas burner, %	-	-	-	-	-	-
Auxiliary burner EE Gas burner, %	n.a.	n.a.	n.a.	n.a.	n.a.	n.a.
Energy consumption for the whole hob, Wh/Kg	n.a.	n.a.	n.a.	n.a.	n.a.	n.a.
Energy efficiency for the whole gas hob, %	57,2	56,9	57,2	57	57	57
FEATURES						
Knobs	*	*	*	*	*	*
Auto ignition	*	*	*	*	*	*
Power lamp indicator	-	-	-	-	-	-
ACCESSORIES						
Enamelled grids	-	-	-	-	-	-
Cast iron grids	*	*	*	*	*	*
Individual grids	-	-	-	-	-	-
Grid accessory	-	-	-	-	-	-
Supplementary small recipient	-	-	-	-	-	-
Cast iron Wok Stands	Available	-	Available	Available	-	Yes
SAFETY SYSTEMS						
Residual heat indicator	-	-	-	-	-	-
Automatic safety device	-	-	-	-	-	-
FINISHING						
Stainless steel frame	-	-	-	-	-	-
Bevelled glass	-	-	-	-	-	-
Frameless glass	-	-	-	-	-	-
Stainless steel	*	*	*	*	*	*
Enamelled Beige / Anthracite	-	-	-	-	-	-



TECHNICAL FEATURES

MODEL	EX 70.1 5G DR	EX 70.1 3G DR	EX 70.1 2G DR	EX 60.1 4G DR	EX 60.1 4G	EX 60.1 3G DR	EX 60.1 3G 1P
EXTERNAL DIMENSIONS							
Width	680	680	680	580	580	580	580
Depth	500	500	500	500	500	500	500
BUILT-IN DIMENSIONS							
Width	553	553	553	553	553	553	553
Height	473	473	473	473	473	473	473
Depth (min.)	52	52	52	52	52	52	52
ELECTRICAL CONNECTION							
Power supply 230 v	*	*	*	*	*	*	*
Frequency Hz	50/60	50/60	50/60	50/60	50/60	50/60	50/60
Maximum nominal power	0,6	0,6	0,6	0,6	0,6	0,6	1500
GAS CONNECTION							
Maximum power kW	11,30	8,55	8,00	9,55	7,30	8,55	5,55
HEATING ELEMENTS							
Electric solid plate Ø 145/1500 W	-	-	-	-	-	-	1
Electric solid plat Ø 145/1000 W	-	-	-	-	-	-	-
Double ring burner, 5,0 kW	-	-	-	-	-	-	-
Double ring burner, 4,00 kW	1	1	2	1	-	1	-
Triple ring burner, 4,00 kW	-	-	-	-	-	-	-
Triple ring burner, 3,50 kW	-	-	-	-	-	-	-
Triple ring burner, 3,10 kW	-	-	-	-	-	-	-
Triple ring burner, 3,80 kW	-	-	-	-	-	-	-
Fish burner, 2,80 kW	-	-	-	-	-	-	-
Fast burner, 3,00 Kw	-	-	-	-	-	-	-
Fast burner, 2,80 kW	1	1	-	1	1	1	1
Fast burner, 2,70 kW	-	-	-	-	-	-	-
Semifast burner, 1,75 kW	2	1	-	1	2	1	1
Semifast burner, 1,50 kW	-	-	-	-	-	-	-
Semifast burner, 1,40 kW	-	-	-	-	-	-	-
Auxiliary burner, 1,00 kW	1	-	-	1	1	-	1
High light ø 180, 1800 W	-	-	-	-	-	-	-
High light ø 145, 1200 W	-	-	-	-	-	-	-
HOB PERFORMANCE (ACCORDING TO EU 66/2014 REGULATION)							
ø21 cm ECElectric cooking-Induction, Wh/Kg	-	-	-	-	-	-	-
ø14,5 cm ECElectric cooking-Induction, Wh/Kg	-	-	-	-	-	-	-
ø18 cm ECElectric cooking-Radiant heater, Wh/Kg	-	-	-	-	-	-	-
ø14,5 cm ECElectric cooking-Radiant heater, Wh/Kg	-	-	-	-	-	-	-
17 x 26,5 cm ECElectric cooking-Radiant heater, Wh/Kg	-	-	-	-	-	-	-
Ø 145 solid plate ECElectric cooking-plate heater, Wh/Kg	-	-	-	-	-	-	198,1
Triple ring burner EE Gas burner, %	-	-	-	-	-	-	-
Double ring burner EE Gas burner, %	58,7	58,7	58,7	58,7	-	58,7	-
Fish burner EE Gas burner, %	-	-	-	-	-	-	-
Fast burner EE Gas burner, %	56,3	56,3	-	56,3	56,3	56,3	56,3
Semi-fast burner EE Gas burner, %	57,0	57,0	-	57,0	57,0	57,0	57,0
Semi-fast reduced burner EE Gas burner, %	-	-	-	-	-	-	-
Auxiliary burner EE Gas burner, %	n.a.	n.a.	n.a.	n.a.	n.a.	n.a.	n.a.
Energy consumption for the whole hob, Wh/Kg	n.a.	n.a.	n.a.	n.a.	n.a.	n.a.	198
Energy efficiency for the whole gas hob, %	57	57	59	57	57	57	57
FEATURES							
Knobs	*	*	*	*	*	*	*
Auto ignition	*	*	*	*	*	*	*
Power lamp indicator	-	-	-	-	-	-	-
ACCESSORIES							
Enamelled grids	-	-	-	-	-	-	-
Cast iron grids	*	*	*	*	*	*	*
Individual grids	-	-	-	-	-	-	-
Grid accessory	-	-	-	-	-	-	-
Supplementary small recipient	-	-	-	-	-	-	-
Cast iron Wok Stands	Available	Yes	Yes	Available	-	Available	-
SAFETY SYSTEMS							
Residual heat indicator	-	-	-	-	-	-	-
Automatic safety device	-	-	-	-	-	-	-
FINISHING							
Stainless steel frame	-	-	-	-	-	-	-
Bevelled glass	-	-	-	-	-	-	-
Frameless glass	-	-	-	-	-	-	-
Stainless steel	*	*	*	*	*	*	*
Enamelled Beige / Anthracite	-	-	-	-	-	-	-

MODEL	EH 60 4G AI AL TR CI	EH 60 4G AI AL TR CI NAT	HLX 60 4G AI AL TR
EXTERNAL DIMENSIONS			
Width	580	580	580
Depth	500	500	500
BUILT-IN DIMENSIONS			
Width	553	553	553
Height	473	473	473
Depth (min.)	83	83	35
ELECTRICAL CONNECTION			
Power supply 230 v	•	•	•
Frequency Hz	50/60	50/60	50/60
Maximum nominal power	0,6	0,6	0,6
GAS CONNECTION			
Maximum power kW	9,25	9,25	8,85
HEATING ELEMENTS			
Electric solid plate Ø 145/1000 W	–	–	–
Double ring burner, 4,00 kW	–	–	–
Triple ring burner, 3,50 kW	1	1	–
Triple ring burner, 3,10 kW	–	–	1
Fast burner, 3,00 Kw	1	1	–
Fast burner, 2,80 kW	–	–	–
Semifast burner, 1,75 kW	1	1	2
Semifast burner, 1,40 kW	–	–	–
Auxiliary burner, 1,00 kW	1	1	1
High light ø 180, 1800 W	–	–	–
High light ø 145, 1200 W	–	–	–
HOB PERFORMANCE (ACCORDING TO EU 66/2014 REGULATION)			
ø21 cm ECElectric cooking–Induction, Wh/Kg	–	–	–
ø14,5 cm ECElectric cooking–Induction, Wh/Kg	–	–	–
ø18 cm ECElectric cooking–Radiant heater, Wh/Kg	–	–	–
ø14,5 cm ECElectric cooking–Radiant heater, Wh/Kg	–	–	–
17 x 26,5 cm ECElectric cooking–Radiant heater, Wh/Kg	–	–	–
Ø 145 solid plate ECElectric cooking–plate heater, Wh/Kg	–	–	–
Triple ring burner EE Gas burner, %	55,2	55,2	54,2
Double ring burner EE Gas burner, %	–	–	–
Fast burner EE Gas burner, %	57,3	57,3	–
Semi-fast burner EE Gas burner, %	58,1	58,1	55,5
Semi-fast reduced burner EE Gas burner, %	–	–	–
Auxiliary burner EE Gas burner, %	n.a.	n.a.	n.a.
Energy consumption for the whole hob, Wh/Kg	n.a.	n.a.	n.a.
Energy efficiency for the whole gas hob, %	56,9	56,9	55,1
FEATURES			
Knobs	•	•	•
Auto ignition	•	•	•
Power lamp indicator	–	–	–
ACCESSORIES			
Enamelled grids	–	–	•
Cast iron grids	•	•	–
Individual grids	–	–	–
Grid accessory	–	–	–
Supplementary small recipient	–	–	–
SAFETY SYSTEMS			
Residual heat indicator	–	–	–
Automatic safety device	•	•	•
FINISHING			
Stainless steel frame	–	–	–
Bevelled glass	–	–	–
Frameless glass	–	–	–
Stainless steel	•	•	•
Enamelled Beige / Anthracite	•	Enamelled Bright cream	–

MODEL	HLX 60 4G AI AL	HLX 60 3G 1P AI AL	HLX 50 4G AI AL
EXTERNAL DIMENSIONS			
Width	580	580	600
Depth	500	500	435
BUILT-IN DIMENSIONS			
Width	553	553	575
Height	473	473	405
Depth (min.)	35	35	35
ELECTRICAL CONNECTION			
Power supply 230 v	•	•	•
Frequency Hz	50/60	50/60	50/60
Maximum nominal power	0,6	1000	0,6
GAS CONNECTION			
Maximum power kW	7,5	5,75	6,8
HEATING ELEMENTS			
Electric solid plate Ø 145/1000 W	–	1	–
Double ring burner, 4,00 kW	–	–	–
Triple ring burner, 3,50 kW	–	–	–
Triple ring burner, 3,10 kW	–	–	–
Fast burner, 3,00 Kw	1	1	1
Fast burner, 2,80 kW	–	–	–
Semifast burner, 1,75 kW	2	1	2
Semifast burner, 1,40 kW	–	–	–
Auxiliary burner, 1,00 kW	1	1	1
High light ø 180, 1800 W	–	–	–
High light ø 145, 1200 W	–	–	–
HOB PERFORMANCE (ACCORDING TO EU 66/2014 REGULATION)			
ø21 cm ECElectric cooking–Induction, Wh/Kg	–	–	–
ø14,5 cm ECElectric cooking–Induction, Wh/Kg	–	–	–
ø18 cm ECElectric cooking–Radiant heater, Wh/Kg	–	–	–
ø14,5 cm ECElectric cooking–Radiant heater, Wh/Kg	–	–	–
17 x 26,5 cm ECElectric cooking–Radiant heater, Wh/Kg	–	–	–
Ø 145 solid plate ECElectric cooking–plate heater, Wh/Kg	–	198,1	–
Triple ring burner EE Gas burner, %	–	–	–
Double ring burner EE Gas burner, %	–	–	–
Fast burner EE Gas burner, %	54,2	54,2	54,2
Semi-fast burner EE Gas burner, %	55,5	55,5	55,5
Semi-fast reduced burner EE Gas burner, %	–	–	–
Auxiliary burner EE Gas burner, %	n.a.	n.a.	n.a.
Energy consumption for the whole hob, Wh/Kg	n.a.	195,0	n.a.
Energy efficiency for the whole gas hob, %	55,1	54,9	55,1
FEATURES			
Knobs	•	•	•
Auto ignition	•	•	•
Power lamp indicator	–	•	–
ACCESSORIES			
Enamelled grids	•	•	•
Cast iron grids	–	–	–
Individual grids	–	–	–
Grid accessory	–	–	–
Supplementary small recipient	–	–	–
SAFETY SYSTEMS			
Residual heat indicator	–	•	–
Automatic safety device	•	•	•
FINISHING			
Stainless steel frame	–	–	–
Bevelled glass	–	–	–
Frameless glass	–	–	–
Stainless steel	•	•	•
Enamelled Beige / Anthracite	–	–	–

MODEL	TPI 380	IR 4200	IRF 3200	IR 3200	VT TC 2P.1	VT TC 2P B
EXTERNAL DIMENSIONS						
Width	380	450	450	300	300	300
Depth	520	520	520	520	520	520
BUILT-IN DIMENSIONS						
Width	360	420	270	270	270	270
Height	490	500	500	500	500	500
Depth (min.)	60	50	50	50	55	55
ELECTRICAL CONNECTION						
Power supply 230 v	•	•	•	•	•	•
Frequency Hz	50/60	50/60	50/60	50/60	50/60	50/60
Maximum nominal power	2800	3200	3200	3200	2900	3000
Wire lenght cm.	110	110	110	110	90	110
GAS CONNECTION						
Maximum power kW	-	-	-	-	-	-
HEATING ELEMENTS						
Flex 235 x 190, 1750 -2200W	-	-	2	-	-	-
Induction Ø 260, 2.100/3000 W	-	1	-	-	-	-
Induction Ø 210, 2.100/3000 W	-	-	-	1	-	-
Induction Ø 145, 1.100/1.800 W	-	1	-	1	-	-
Induction Ø 145, 1.400 W	2	-	-	-	-	-
High light ø 120/180, 700/1.700 W	-	-	-	-	1	-
High light ø 180, 1.800 W	-	-	-	-	-	1
High light ø 145, 1.200 W	-	-	-	-	1	1
DUAL double ring burner /8000 w	-	-	-	-	-	-
Double ring burner 4,0 kW	-	-	-	-	-	-
Fast burner, 2,80 kW	-	-	-	-	-	-
Auxiliary burner, 1,00 kW	-	-	-	-	-	-
HOB PERFORMANCE (ACCORDING TO EU 66/2014 REGULATION)						
ø26 cm ECElectric cooking-Induction, Wh/Kg	-	176,5	-	-	-	-
ø21 cm ECElectric cooking-Induction, Wh/Kg	-	-	-	180	-	-
ø14,5 cm ECElectric cooking-Induction, Wh/Kg	-	198,4	-	198,4	-	-
23,5 x 19 cm ECElectric cooking-Induction, Wh/Kg	-	-	Area Flex=190,3 Oval single= 178	-	-	-
ø12/18 cm ECElectric cooking-Radiant heater, Wh/Kg	-	-	-	-	192,33	-
ø14,5 cm ECElectric cooking-Radiant heater, Wh/Kg	-	-	-	-	188,02	188,02
ø18 cm ECElectric cooking-Radiant heater, Wh/Kg	-	-	-	-	-	188,33
Triple ring burner EE Gas burner, %	-	-	-	-	-	-
Double ring burner EE Gas burner, %	-	-	-	-	-	-
Fast burner EE Gas burner, %	-	-	-	-	-	-
Energy consumption for the whole hob, Wh/Kg	n.a.	187,4	190,3	189,2	190,175	188,175
Energy efficiency for the whole gas hob, %	n.a.	-	-	-	-	-
FEATURES						
Touch control	•	•	•	•	•	•
Cooking programming	•	•	•	•	•	•
Pan optimization system	-	•	•	•	-	-
Timer	-	•	•	•	•	•
Power function	-	•	•	•	-	-
Burst of cooking function	-	-	-	-	•	-
Pan detector	-	•	•	•	-	-
Low temp function	-	-	•	-	-	-
Auto ignition	-	-	-	-	-	-
Power lamp indicator	-	-	-	-	-	-
Knobs	-	-	-	-	-	-
ACCESSORIES						
Cast iron grids	-	-	-	-	-	-
SAFETY SYSTEMS						
Residual heat indicator	•	•	•	•	•	•
Automatic safety device	•	-	•	-	•	-
FINISHING						
Stainless steel frame	-	-	-	-	-	-
Bevelled glass	-	•	•	•	•	•
Frameless	-	-	-	-	-	•

MODEL	VT CM 30 2P	VM 30 2P-T	VM 30 2P	CGW LUX 30 1G AI AL DR 8KW CI	CGW LUX 30.1G AI AL DR CI	CGW LUX 30.1 2G AI AL CI
EXTERNAL DIMENSIONS						
Width	300	300	300	380	300	300
Depth	520	510	510	505	520	520
BUILT-IN DIMENSIONS						
Width	270	280	280	370	282	282
Height	500	490	490	482	482	482
Depth (min.)	55	40	40	62	50	50
ELECTRICAL CONNECTION						
Power supply 230 v	•	•	•	•	•	•
Frequency Hz	50/60	50/60	50/60	50/60	50/60	50/60
Maximum nominal power	3000	2900	2900	-	-	-
Wire lenght cm.	110	135	135	135	135	135
GAS CONNECTION						
Maximum power kW	-	-	-	8,00	4,00	3,80
HEATING ELEMENTS						
Flex 235 x 190, 1750 -2200W	-	-	-	-	-	-
Induction Ø 260, 2.100/3000 W	-	-	-	-	-	-
Induction Ø 210, 2.100/3000 W	-	-	-	-	-	-
Induction Ø 145, 1.100/1.800 W	-	-	-	-	-	-
Induction Ø 145, 1.400 W	-	-	-	-	-	-
High light ø 120/180, 700/1.700 W	-	-	-	-	-	-
High light ø 180, 1.800 W	1	1	1	-	-	-
High light ø 145, 1.200 W	1	1	1	-	-	-
DUAL double ring burner /8000 w	-	-	-	1	-	-
Double ring burner 4,0 kW	-	-	-	-	1	-
Fast burner, 2,80 kW	-	-	-	-	-	1
Auxiliary burner, 1,00 kW	-	-	-	-	-	1
HOB PERFORMANCE (ACCORDING TO EU 66/2014 REGULATION)						
ø26 cm ECElectric cooking-Induction, Wh/Kg	-	-	-	-	-	-
ø21 cm ECElectric cooking-Induction, Wh/Kg	-	-	-	-	-	-
ø14,5 cm ECElectric cooking-Induction, Wh/Kg	-	-	-	-	-	-
23,5 x 19 cm ECElectric cooking-Induction, Wh/Kg	-	-	-	-	-	-
ø12/18 cm ECElectric cooking-Radiant heater, Wh/Kg	-	-	-	-	-	-
ø14,5 cm ECElectric cooking-Radiant heater, Wh/Kg	188,02	188,02	188,02	-	-	-
ø18 cm ECElectric cooking-Radiant heater, Wh/Kg	188,33	188,33	188,33	-	-	-
Triple ring burner EE Gas burner, %	-	-	-	-	54,3	-
Double ring burner EE Gas burner, %	-	-	-	55,2	-	-
Fast burner EE Gas burner, %	-	-	-	-	-	59,8
Energy consumption for the whole hob, Wh/Kg	188,175	188,175	188,175	n.a.	n.a.	n.a.
Energy efficiency for the whole gas hob, %	-	-	-	55,2	54,3	59,8
FEATURES						
Touch control	-	-	-	-	-	-
Cooking programming	-	-	-	-	-	-
Pan optimization system	-	-	-	-	-	-
Timer	-	•	-	-	-	-
Power function	-	-	-	-	-	-
Burst of cooking function	-	-	-	-	-	-
Pan detector	-	-	-	-	-	-
Low temp function	-	-	-	-	-	-
Auto ignition	-	-	-	•	•	•
Power lamp indicator	-	•	•	-	-	-
Knobs	•	•	•	•	•	•
ACCESSORIES						
Cast iron grids	-	-	-	•	•	•
SAFETY SYSTEMS						
Residual heat indicator	•	-	-	-	-	-
Automatic safety device	-	-	-	•	•	•
FINISHING						
Stainless steel frame	-	•	•	-	-	-
Bevelled glass	•	-	-	•	•	•
Frameless	-	-	-	-	-	-

MODEL	EFX 30 1G AI AL DR CI	EFX 30 2G AI AL	EFX 30 1P	EFX 30 1P-T	EFX 30 2P
EXTERNAL DIMENSIONS					
Width	305	305	305	305	305
Depth	510	510	510	510	510
BUILT-IN DIMENSIONS					
Width	282	282	282	282	282
Height	482	482	482	482	482
Depth (min.)	45	45	45	45	45
ELECTRICAL CONNECTION					
Power supply 230 v	•	•	•	•	•
Frequency Hz	50/60	50/60	50/60	50/60	50/60
Maximum nominal power	–	–	1500	1500	1500
Wire lenght cm.	135	135	135	135	135
GAS CONNECTION					
Maximum power kW	4,00	4,00	–	–	–
HEATING ELEMENTS					
Oval Induction 235x190/2.200 W	–	–	–	–	–
High light grill, 2.500w	–	–	–	–	–
High light ø 180, 1.800 W	–	–	1	1	–
High light ø 160, 1500 W	–	–	–	–	–
High light ø 145, 1.200 W	–	–	–	–	–
Electric resistance	–	–	–	–	–
Teppanyaki	–	–	–	–	–
Electric solid plate ø 180/ 2000 W	–	–	1	1	1
Electric solid plat Ø 180/1500 W	–	–	–	–	–
Electric solid plat Ø 145/1500 W	–	–	–	–	1
Double ring burner 4,0 kW	1	–	–	–	–
Fast burner, 3,00 kW	–	1	–	–	–
Auxiliary burner, 1,00 kW	–	1	–	–	–
HOB PERFORMANCE (ACCORDING TO EU 66/2014 REGULATION)					
ø14,5 cm ECElectric cooking-Radiant heater, Wh/Kg	-	-	-	-	-
ø18 cm ECElectric cooking-Radiant heater, Wh/Kg	-	-	-	-	-
Oval 17x27 cm ECElectric cooking-Radiant heater, Wh/Kg	-	-	-	-	-
Ø 180 solid plate ECElectric cooking-plate heater, Wh/Kg	-	-	197	197	197
Ø 145 solid plate ECElectric cooking-plate heater, Wh/Kg	-	-	-	-	198,1
Double ring burner EE Gas burner, %	56,6	-	-	-	-
Fast burner EE Gas burner, %	-	58,8	-	-	-
Auxiliary burner EE Gas burner, %	-	n.a.	-	-	-
Energy consumption for the whole hob, Wh/Kg	n.a.	n.a.	197	197	197,55
Energy efficiency for the whole gas hob, %	56,6	58,8	-	-	-
FEATURES					
Timer	–	–	–	–	–
Power lamp indicator	–	–	–	–	–
Knobs	•	•	•	•	•
ACCESSORIES					
Enamelled grids	–	–	–	–	–
Cast iron grids	•	•	–	–	–
SAFETY SYSTEMS					
Automatic safety device	•	•	–	–	–
FINISHING					
Stainless steel frame	–	–	–	–	–
Stainless steel	•	•	•	•	•

MODEL	EFX 30 2P-T	EFX 30 2H	EFX 30 2H-T	EFX 30 1H	EFX 30 1H-T
EXTERNAL DIMENSIONS					
Width	305	305	305	305	305
Depth	510	510	510	510	510
BUILT-IN DIMENSIONS					
Width	282	282	282	282	282
Height	482	482	482	482	482
Depth (min.)	45	45	45	45	45
ELECTRICAL CONNECTION					
Power supply 230 v	•	•	•	•	•
Frequency Hz	50/60	50/60	50/60	50/60	50/60
Maximum nominal power	3500	3000	3000	2200	2200
Wire lenght cm.	135	135	135	135	135
GAS CONNECTION					
Maximum power kW	–	–	–	–	–
HEATING ELEMENTS					
Oval Induction 235x190/2.200 W	–	–	–	1	1
High light grill, 2.500w	–	–	–	–	–
High light ø 180, 1.800 W	–	1	1	–	–
High light ø 160, 1500 W	–	–	–	–	–
High light ø 145, 1.200 W	–	1	1	–	–
Electric resistance	–	–	–	–	–
Teppanyaki	–	–	–	–	–
Electric solid plate ø 180/ 2000 W	1	–	–	–	–
Electric solid plat Ø 180/1500 W	–	–	–	–	–
Electric solid plat Ø 145/1500 W	1	–	–	–	–
Double ring burner 4,0 kW	–	–	–	–	–
Fast burner, 3,00 kW	–	–	–	–	–
Auxiliary burner, 1,00 kW	–	–	–	–	–
HOB PERFORMANCE (ACCORDING TO EU 66/2014 REGULATION)					
ø14,5 cm ECElectric cooking-Radiant heater, Wh/Kg	-	185,5	185,5	-	-
ø18 cm ECElectric cooking-Radiant heater, Wh/Kg	-	185,9	185,9	-	-
Oval 17x27 cm ECElectric cooking-Radiant heater, Wh/Kg	-	-	-	188,67	188,67
Ø 180 solid plate ECElectric cooking-plate heater, Wh/Kg	197	-	-	-	-
Ø 145 solid plate ECElectric cooking-plate heater, Wh/Kg	198,1	-	-	-	-
Double ring burner EE Gas burner, %	-	-	-	-	-
Fast burner EE Gas burner, %	-	-	-	-	-
Auxiliary burner EE Gas burner, %	-	-	-	-	-
Energy consumption for the whole hob, Wh/Kg	197,55	185,7	185,7	188,67	188,67
Energy efficiency for the whole gas hob, %	-	-	-	-	-
FEATURES					
Timer	•	–	•	–	•
Power lamp indicator	•	•	•	•	•
Knobs	•	•	•	•	•
ACCESSORIES					
Enamelled grids	–	–	–	–	–
Cast iron grids	–	–	–	–	–
SAFETY SYSTEMS					
Automatic safety device	–	–	–	•	•
FINISHING					
Stainless steel frame	–	–	–	–	–
Stainless steel	•	–	–	•	•

MODEL	EFX 30 1G	EFX 30 1G-T	EFX 30 GRILL	EFX 30 FRYER
EXTERNAL DIMENSIONS				
Width	305	305	305	305
Depth	510	510	510	510
BUILT-IN DIMENSIONS				
Width	282	282	282	282
Height	482	482	482	482
Depth (min.)	45	45	160	160
ELECTRICAL CONNECTION				
Power supply 230 v	•	•	•	•
Frequency Hz	50/60	50/60	50/60	50/60
Maximum nominal power	2500	2500	2400	2300
Wire lenght cm.	135	135	135	135
GAS CONNECTION				
Maximum power kW	–	–	–	–
HEATING ELEMENTS				
Oval Induction 235x190/2.200 W	–	–	–	–
High light grill, 2.500w	1	1	–	–
High light ø 180, 1.800 W	–	–	–	–
High light ø 160, 1500 W	–	–	–	–
High light ø 145, 1.200 W	–	–	–	–
Electric resistance	–	–	1	1
Teppanyaki	–	–	–	–
Electric solid plate ø 180/ 2000 W	–	–	–	–
Electric solid plat Ø 180/1500 W	–	–	–	–
Electric solid plat Ø 145/1500 W	–	–	–	–
Double ring burner 4,0 kW	–	–	–	–
Fast burner, 3,00 kW	–	–	–	–
Auxiliary burner, 1,00 kW	–	–	–	–
HOB PERFORMANCE (ACCORDING TO EU 66/2014 REGULATION)				
ø14,5 cm ECElectric cooking-Radiant heater, Wh/Kg	-	-	-	-
ø18 cm ECElectric cooking-Radiant heater, Wh/Kg	-	-	-	-
Oval 17x27 cm ECElectric cooking-Radiant heater, Wh/Kg	-	-	-	-
Ø 180 solid plate ECElectric cooking-plate heater, Wh/Kg	-	-	-	-
Ø 145 solid plate ECElectric cooking-plate heater, Wh/Kg	-	-	-	-
Double ring burner EE Gas burner, %	-	-	-	-
Fast burner EE Gas burner, %	-	-	-	-
Auxiliary burner EE Gas burner, %	-	-	-	-
Energy consumption for the whole hob, Wh/Kg	n.a.	n.a.	n.a.	n.a.
Energy efficiency for the whole gas hob, %	n.a.	n.a.	n.a.	n.a.
FEATURES				
Timer	–	•	–	–
Power lamp indicator	•	•	•	•
Knobs	•	•	•	•
ACCESSORIES				
Enamelled grids	–	–	–	–
Cast iron grids	–	–	–	–
SAFETY SYSTEMS				
Automatic safety device	•	•	•	•
FINISHING				
Stainless steel frame	–	–	–	–
Stainless steel	•	•	•	•

MODEL	EFX 30 TEPPANYAKI	EM 30 2G AI AL	EM 30 2P-T	EM 30 2P
EXTERNAL DIMENSIONS				
Width	305	300	300	300
Depth	510	510	510	510
BUILT-IN DIMENSIONS				
Width	282	280	280	280
Height	482	490	490	490
Depth (min.)	60	37	37	37
ELECTRICAL CONNECTION				
Power supply 230 v	•	•	•	•
Frequency Hz	50/60	50/60	50/60	50/60
Maximum nominal power	2400	0,6	3000	3000
Wire lenght cm.	135	135	135	135
GAS CONNECTION				
Maximum power kW	–	4,00	–	–
HEATING ELEMENTS				
Oval Induction 235x190/2.200 W	–	–	–	–
High light grill, 2.500w	–	–	–	–
High light ø 180, 1.800 W	–	–	–	–
High light ø 160, 1500 W	–	–	–	–
High light ø 145, 1.200 W	–	–	–	–
Electric resistance	–	–	–	–
Teppanyaki	1	–	–	–
Electric solid plate ø 180/ 2000 W	–	–	–	–
Electric solid plat Ø 180/1500 W	–	–	1	1
Electric solid plat Ø 145/1500 W	–	–	1	1
Double ring burner 4,0 kW	–	–	–	–
Fast burner, 3,00 kW	–	1	–	–
Auxiliary burner, 1,00 kW	–	1	–	–
HOB PERFORMANCE (ACCORDING TO EU 66/2014 REGULATION)				
ø14,5 cm ECElectric cooking-Radiant heater, Wh/Kg	-	-	-	-
ø18 cm ECElectric cooking-Radiant heater, Wh/Kg	-	-	-	-
Oval 17x27 cm ECElectric cooking-Radiant heater, Wh/Kg	-	-	-	-
Ø 180 solid plate ECElectric cooking-plate heater, Wh/Kg	-	-	198,84	198,84
Ø 145 solid plate ECElectric cooking-plate heater, Wh/Kg	-	-	200	200
Double ring burner EE Gas burner, %	-	-	-	-
Fast burner EE Gas burner, %	-	55,3	-	-
Auxiliary burner EE Gas burner, %	-	n.a.	-	-
Energy consumption for the whole hob, Wh/Kg	n.a.	-	199,42	199,42
Energy efficiency for the whole gas hob, %	n.a.	55,3	-	-
FEATURES				
Timer	–	–	•	–
Power lamp indicator	•	–	•	•
Knobs	•	•	•	•
ACCESSORIES				
Enamelled grids	–	•	–	–
Cast iron grids	–	–	–	–
SAFETY SYSTEMS				
Automatic safety device	•	•	–	–
FINISHING				
Stainless steel frame	–	•	•	•
Stainless steel	•	•	–	–